Form 3160-3 (August 1999)	CATECO CONTRACTOR OF THE CONTR	FORM APPRO OMB No. 1004- Expires November	0136
UNITED ST DEPARTMENT OF T BUREAU OF LAND	THE INTERIOR A 9 10 11 16 15 A	5. Lease Serial No. SF - 078051	
APPLICATION FOR PERMIT	TO DRILL OR REENTER 2001	6. If Indian, Allottee or Tribe N	Vame
la. Type of Work: 🛛 DRILL 🔲 REENTER	Control S	7. If Unit or CA Agreement, N	ame and No.
1b. Type of Well: ☐ Oil Well Gas Well ☐ Oth	ner Single Zone Multiple Zone	Lease Name and Well No. MUDGE LS 22M	
2. Name of Operator Contact: AMOCO PRODUCTION COMPANY	MARY CORLEY E-Mail: corleyml@bp.com	9. API Well No. 30 -045-3	30757
3a. Address P.O. BOX 3092 HOUSTON, TX 77253	3b. Phone No. (include area code) Ph: 281.366.4491 Fx: 281.366.0700	10. Field and Pool, or Explorat BASIN DAKOTA/BLAN	
4. Location of Well (Report location clearly and in accorda	ince with any State requirements.*)	11. Sec., T., R., M., or Blk. and	Survey or Area
At surface SESE Lot P 1120FSL 860F At proposed prod. zone	FEL 36.55400 N Lat, 107.59400 W Lon	ρ Sec 4 T31N R11W Me	r NMP
14. Distance in miles and direction from nearest town or post 9 MILES FROM AZTEC	office*	12. County or Parish SAN JUAN	13. State NM
15. Distance from proposed location to nearest property or lease line, ft. (Also to nearest drig, unit line, if any)	16. No. of Acres in Lease	17. Spacing Unit dedicated to t	his well
860	309.31	309.31	
 Distance from proposed location to nearest well, drilling, completed, applied for, on this lease, ft. 	19. Proposed Depth	20. BLM/BIA Bond No. on file	2
completed, applied 101, oil tills fease, in	7530 MD		
21. Elevations (Show whether DF, KB, RT, GL, etc. 6075 GL	22. Approximate date work will start 08/27/2001	23. Estimated duration	
	24. Attachments		
The following, completed in accordance with the requirements of	f Onshore Oil and Gas Order No. 1, shall be attached to	this form:	
 Well plat certified by a registered surveyor. A Drilling Plan. A Surface Use Plan (if the location is on National Forest Syst SUPO shall be filed with the appropriate Forest Service Of 	tem Lands, the Item 20 above). 5. Operator certification	ions unless covered by an existing to	
25. Signature	Name (Printed/Typed) MARY CORLEY		Date 07/27/2001
Title AUTHORIZED REPRESENTATIVE			
Approved by (Signature)	Name (Printed/Typed) Dabid T. Mankie		Date / 10/81
AFM Minerals	Office FFO		
Application approval does not warrant or certify the applicant he operations thereon. Conditions of approval, if any, are attached.	olds legal or equitable title to those rights in the subject	lease which would entitle the applic	cant to conduct
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, States any false, fictitious or fraudulent statements or representa	make it a crime for any person knowingly and willfully tions as to any matter within its jurisdiction.	to make to any department or agen	cy of the United

Additional Operator Remarks (see next page)

Electronic Submission #6014 verified by the BLM Well Information System
For AMOCO PRODUCTION COMPANY, sent to the Farmington
Committed to AFMSS for processing by Maurice Johnson on 08/01/2001 ()
procedural review pursuant to 43 CFR 3185.3

and appeal pursuant to 43 CFR \$166.4.

DRIELING INFERAJIONS AUTHORIZED ARE SUBJECT TO COMPEIANCE WITH ATTACHED "GENERAL REQUIREMENTS".

** ORIGINAL ** ORIGINAL ** ORIGINAL ** ORIGINAL ** ORIGINAL **

PO Box 1980, Hobbs NM 88241-1980 District II

PO Drawer KK, Artesia, NM 87211 0719

District III

1000 Río Brazos Rd., Aztec, NM 87410 District IV

PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION PO Box 2088 Santa Fe, NM 87504-2088

Form C-102 Revised February 21, 1994 Instructions on back Submit to Appropriate District Office State Lease - 4 Copies

Fee Lease - 3 Copies

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number	r ² Pool Code	A 1 Pool Name	
30-045-30	757 71599 - 72319	BASIN DAKOTA & BLANCO	MESAVERDS
' Property Code	3]	Property Name	Well Number
000911	Mudge LS	# 22M	
7 OGRID No.	* (Operator Name	" Elevation
000718	AMOCO PRODUCTION	ON COMPANY	6075


¹⁰ Surface Location


UL or Lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	4	31 N	11 W		1120	SOUTH	860	EAST	SAN JUAN
									

11 Bottom Hole Location If Different From Surface

7 UL or lot no.	Section	Township	Range	Lot ida	Feet from the	North/South line	Foot from the	East/West line	County
309.31	Join	or Infill 14	Consolidatio	n Code B	Order No.		<u> </u>		

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION





AMOCO PRODUCTION COMPANY DRILLING AND COMPLETION PROGRAM

Prospect Name: Mudge LS

Lease: MUDGE LS
County: San Juan

State: New Mexico
Date: July 27, 2001

Well No: 22M

Surface Location: 4-31N-11W, 1120 FSL,860 FEL

Field: Blanco Mesaverde/Basin Dakota

OBJECTIVE: Drill 450' belo	ow the base of the Greenhorn Limestone, set	41/2" production casing, §	Stimulate LS	, CH, MF, PL and D	K intervals	
METH	APPROXIMATE	APPROXIMATE DEPTHS OF GEOLOGICAL MARKER				
TYPE OF TOOLS	DEPTH OF DRILLING	Estimated GL:	6075	Estimate	d KB: _60	089
Rotary	0 - TD	MARKER		SUBSEA	MEAS	. DEPTH
L	OG PROGRAM	Ojo Alamo		4320		1769
TYPE	DEPTH INVERAL	Fruitland Coal	*	3845		2564
OPEN HOLE		Pictured Cliffs	*	3323		2766
GR-Induction	TD to 7" shoe	Lewis Shale	#	2968		3121
Density/Neutron	TD to 7" shoe	Cliff House	#	1589		4500
		Menefee Shale	#	1486	;	4603
CASED HOLE		Point Lookout	#	1084		5005
GR-CCL-TDT	TDT TD to 7" shoe	Mancos		716		5373
CBL	Identify 4 1/2" cement top	Greenhorn		-947	·	7035
		Bentonite Marker	1 1	-991		7080
REMARKS:		Two Wells	#	-1057	•	7146
- Please report any flares (magnitude & duration).	Dakota MB	#	-1162	:	7251
. ,	,	Burro Canyon	*	-1295		7384
		Morrison	*	-1345		7434
		TOTAL DEPTH		-1441		7530
		# Probable compl	etion inter	val * Possib	le Pay	
SI	PECIAL TESTS	DRILL CUTTIN	G SAMPI	ES DR	LLING T	ME
TYPE		FREQUENCY	DEPTH	FREQUE	NCY [DEPTH
None		10 feet	Production	hole Geologra	oh ()-TD
REMARKS:						

	ROGRAM: c. Interval		Type Mud	Weight, #/ga	Vis, sec/qt	W/L cc's/30 min	Other Specification
0	- 200		Spud	8.6-9.2			
200	- 3221	(1)	Water/LSND	8.6-9.2		<6	
3221	- 7384		Gas/Air/N2/Mist	Volume su	fficient to mainta	ain a stable and clean	wellbore
7384	7530	(2)	LSND	9.0-9.2		<6	·

REMARKS:

- (1) The hole will require sweeps to keep unloaded while fresh water drilling. Let hole conditions dictate frequency.
- (2) Mud up 50' above Morrison +/-.

CASING PROGRAM: (Normally, tubular goods allocation letter specifies casing sizes to be used. Hole sizes will be governed by Contract)										
Casing String	Estimated Depth	Casing Size	Grade	Weight	Hole Size	Landing Pt, Cmt, Etc.				
Surface/Conductor	200	9 5/8"	H-40 ST&C	32#	12.25"	1				
Intermediate 1	3221	7"	J/K-55 ST&C	20#	8.75"	1,2				
Production	7530.2	4 1/2"	J-55	11.6#	6.25"	3				

REMARKS:

- (1) Circulate Cement to Surface
- (2) Set casing 100' into Lewis Shale
- (3) Bring cement 100' above 7" shoe

CORING PROGRAM:

None

COMPLETION PROGRAM:

Rigless, 4-6 Stage Limited Entry Hydraulic Frac

GENERAL REMARKS:

Notify BLM/NMOCD 24 hours prior to Spud, BOP testing, and Casing and Cementing.

Form 46 Reviewed by:	ing program reviewed by: N/A	
PREPARED BY:	APPROVED:	DATE:
		21 June 2001
HGJ/MNP		Version 1.0

Amoco Production Company BOP Pressure Testing Requirements

Well Name:

MUDGE LS 22M

County:

San Juan

State: New Mexico

Formation	TVD	Anticipated Bottom Hole Pressure	Maximum Anticipated Surface-Pressure **
Ojo Alamo	1769		
Fruitland Coal	2564		
PC	2766		
Lewis Shale	3121		
Cliff House	4500	500	0
Menefee Shale	4603		
Point Lookout	5005	600	0
Mancos	5373		
Dakota	7146	2600	1418

** Note: Determined using the following formula: ABHP - (.22 * TVD) = ASP

Requested BOP Pressure Test Exception: 3000 PSI

SAN JUAN BASIN Dakota Formation Pressure Control Equipment

Background

The objective Dakota formation maximum surface pressure is anticipated to be less than 1000 PSI, based on shut-in surface pressures from adjacent wells. Pressure control equipment working pressure minimum requirements are therefore 2000 PSI. Equipment to be used will conform to API RP-53 (Figure 2.C.2) for a 2000 PSI system per Federal Onshore Order No. 2. Due to available conventional equipment within the area, 3000 PSI rated pressure control equipment will typically be utilized in a double ram type arrangement. Regional drilling rights to be utilized have substructure height limitations which exclude the use of annular preventers; therefore a rotating head will be installed above these rams. This pressure control equipment will be utilized for conventional drilling below conductor to total depth in the Basin Dakota. No abnormal temperature, pressure, or H2S anticipated.

Equipment Specification

Interval

BOP Equipment

Below conductor casing to total depth

11" nominal or 7 1/16",3000 PSI double ram preventer with rotating head.

All ram type preventers and related control equipment will be hydraulically tested to 250 PSI (low pressure) and 2000 PSI (high pressure), upon installation, following any repairs or equipment replacements, or at 30 day intervals. Accessories to BOP equipment will include kelly cock, upper kelly cock with a handle available, floor safety valves and choke manifold which will also be tested to equivalent pressure.

Cementing Program

Well Name: Location: County: State:	Mudge LS 22M 4-31N-11W, 11 San Juan New Mexico		EL		Field: API No. Well Flac Formation: KB Elev (est) GL Elev. (est)	Blanco Mesav Dakota Mesa\ 6089	9	ota
Casing Program	n:						-de-	
Casing String	Est. Depth	Hole Size	Casing Size	Thread	TOC	Stage Tool	Cmt Cir. Out	
	(ft.)	(in.)	(in.)		(ft.)	Or TOL (ft.)	(bbl.)	
Surface	200	12.25	9.625	ST&C	Surface	NA		
Intermediate	3221	8.75	7	LT&C	Surface	NA		
Production -	7530	6.25	4.5	?	3121	NA		
Casing Propert			Factor Included)	Durat	Collanas	Joint St.	Capacity D	rift
Casing String	Size	Weight	Grade	Burst (psi.)	Collapse (psi.)	(1000 lbs.)	, ,	n.)
Cf	(in.) 9.62	(lb/ft)	2 H-40	(psi.) 3370				8.845
Surface Intermediate	9.02		2 n-40 0 K-55	3740				6.456
Production -	4		6 J-55	5350				3.875
Production -	4	.5 11.	o J-55	5550	490	0 13	0.0100	0.010
Mud Program			- ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,,					
Apx. Interval	Mud Type	Mud Weight	ł	Recomm	nended Mud Prop	erties Prio Ceme	enting:	
(ft.)	••			PV	<20			
. ,				YP	<10			
0 - SCP	Water/Spud	8.6-9.	2	Fluid Los	ss<15			
SCP - ICP	Water/LSND	8.6-9.	2					
ICP - ICP2	Gas/Air Mist	N.	<u> </u>					
ICP2 - TD	LSND	8.6 - 9.	2					
Cementing Prog	ıram:							
			Surface		Intermediate		Production	
Excess %, Bit			100%		80		10	
			NA		NA		30	
Excess %, Calip					400		460	
Excess %, Calip BHST (est deg.			60	r	120	·_	160	anta
Excess %, Calip BHST (est deg. Pipe Movement	F)		60 NA	F	Rotate/Reciproca	te	Rotate/Recipro	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm.	F))		60 NA 7	F	Rotate/Reciproca 4	te	Rotate/Recipro	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recommen	F)) nded (bpm)		60 NA 7 6	F	Rotate/Reciproca 4 4	te	Rotate/Recipro 2 2	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recommer Pressure, Max (F)) nded (bpm)		60 NA 7 6 200	F	Rotate/Reciproca 4 4 2000	te	Rotate/Reciprod 2 2 2000	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recommer Pressure, Max (Shoe Joint	F)) nded (bpm)		60 NA 7 6 200 40	F	Rotate/Reciproca 4 4 2000 80	te	Rotate/Recipro- 2 2 2000 40	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recomment Pressure, Max (g Shoe Joint Batch Mix	F)) nded (bpm) psi)		60 NA 7 6 200 40 NA	F	Rotate/Reciproca 4 4 2000 80 NA	te	Rotate/Recipro 2 2 2000 40 NA	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recomment Pressure, Max (s Shoe Joint Batch Mix Circulating prior	F)) nded (bpm) psi) cmtng (hr)		60 NA 7 6 200 40 NA 0.5	F	Rotate/Reciproca 4 4 2000 80 NA 1.5	te	Rotate/Recipro- 2 2 2000 40	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recomment Pressure, Max (g. Shoe Joint Batch Mix Circulating prior Time Between S	F)) nded (bpm) psi) cmtng (hr) Stages, (hr)		60 NA 7 6 200 40 NA 0.5 NA	F	Rotate/Reciproca 4 4 2000 80 NA 1.5 NA	te	Rotate/Recipro 2 2 2000 40 NA 2 NA	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recomment Pressure, Max (s Shoe Joint Batch Mix Circulating prior	F)) nded (bpm) psi) cmtng (hr) Stages, (hr) ons	upumps and lin	60 NA 7 6 200 40 NA 0.5 NA	F	Rotate/Reciproca 4 4 2000 80 NA 1.5	te	Rotate/Recipro 2 2 2000 40 NA 2	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recomment Pressure, Max (g. Shoe Joint Batch Mix Circulating prior Time Between S	F)) nded (bpm) psi) cmtng (hr) Stages, (hr)		60 NA 7 6 200 40 NA 0.5 NA	F	Rotate/Reciproca 4 4 2000 80 NA 1.5 NA	te	Rotate/Recipro 2 2 2000 40 NA 2 NA	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recomment Pressure, Max (g. Shoe Joint Batch Mix Circulating prior Time Between S	F)) nded (bpm) psi) cmtng (hr) Stages, (hr) ons 1. Do not wash	s and lines.	60 NA 7 6 200 40 NA 0.5 NA	F	Rotate/Reciproca 4 4 2000 80 NA 1.5 NA	te	Rotate/Recipro 2 2 2000 40 NA 2 NA	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recomment Pressure, Max (g. Shoe Joint Batch Mix Circulating prior Time Between S	F)) nded (bpm) psi) cmtng (hr) Stages, (hr) ons 1. Do not wash 2. Wash pump	s and lines.	60 NA 7 6 200 40 NA 0.5 NA 1,6,7	F	Rotate/Reciproca 4 4 2000 80 NA 1.5 NA	te	Rotate/Recipro 2 2 2000 40 NA 2 NA	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recomment Pressure, Max (g. Shoe Joint Batch Mix Circulating prior Time Between S	F)) nded (bpm) psi) cmtng (hr) Stages, (hr) ons 1. Do not wash 2. Wash pump: 3. Reverse out 4. Run Blend T	s and lines. est on Cemen	60 NA 7 6 200 40 NA 0.5 NA 1,6,7		Rotate/Reciproca 4 4 2000 80 NA 1.5 NA	te	Rotate/Recipro 2 2 2000 40 NA 2 NA	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recomment Pressure, Max (g. Shoe Joint Batch Mix Circulating prior Time Between S	F)) nded (bpm) psi) cmtng (hr) Stages, (hr) ons 1. Do not wash 2. Wash pump: 3. Reverse out 4. Run Blend T 5. Record Rate	s and lines. est on Cemen e, Pressure, an	60 NA 7 6 200 40 NA 0.5 NA 1,6,7	disk	Rotate/Reciproca 4 4 2000 80 NA 1.5 NA	te	Rotate/Recipro 2 2 2000 40 NA 2 NA	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recomment Pressure, Max (g. Shoe Joint Batch Mix Circulating prior Time Between S	F)) nded (bpm) psi) cmtng (hr) Stages, (hr) ons 1. Do not wash 2. Wash pump 3. Reverse out 4. Run Blend T 5. Record Rate 6. Confirm den	s and lines. Test on Cemente, Pressure, an sitometer with	60 NA 7 6 200 40 NA 0.5 NA 1,6,7 nes.	disk scales	Rotate/Reciproca 4 4 2000 80 NA 1.5 NA	te	Rotate/Recipro 2 2 2000 40 NA 2 NA	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recomment Pressure, Max (g. Shoe Joint Batch Mix Circulating prior Time Between S	F)) nded (bpm) psi) cmtng (hr) Stages, (hr) ons 1. Do not wash 2. Wash pump 3. Reverse out 4. Run Blend T 5. Record Rate 6. Confirm den 7. 1" cement to	s and lines. Test on Cement e, Pressure, an sitometer with o surface if cen	60 NA 7 6 200 40 NA 0.5 NA 1,6,7 nes.	disk scales ted.	Rotate/Reciproca 4 4 2000 80 NA 1.5 NA 1,6,8		Rotate/Recipro 2 2 2000 40 NA 2 NA	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recommer Pressure, Max (construction) Shoe Joint Batch Mix Circulating prior Time Between S Special Instruction	F)) nded (bpm) psi) cmtng (hr) Stages, (hr) ons 1. Do not wash 2. Wash pump 3. Reverse out 4. Run Blend T 5. Record Rate 6. Confirm den 7. 1" cement to	s and lines. Test on Cement e, Pressure, an sitometer with o surface if cen	60 NA 7 6 200 40 NA 0.5 NA 1,6,7 nes.	disk scales ted.	Rotate/Reciproca 4 4 2000 80 NA 1.5 NA 1,6,8		Rotate/Recipro 2 2 2000 40 NA 2 NA	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recomment Pressure, Max (g. Shoe Joint Batch Mix Circulating prior Time Between S	F)) nded (bpm) psi) cmtng (hr) Stages, (hr) ons 1. Do not wash 2. Wash pump: 3. Reverse out 4. Run Blend T 5. Record Rate 6. Confirm den 7. 1" cement to 8. If cement is	s and lines. Test on Cemen e, Pressure, an esitometer with es surface if cen not circulated t	60 NA 7 6 200 40 NA 0.5 NA 1,6,7 es. t d Density on 3.5" pressurized mud nent is not circula o surface, run ter	disk scales ted. np. survey	Rotate/Reciproca 4 4 2000 80 NA 1.5 NA 1,6,8	anding plug.	Rotate/Recipro 2 2 2000 40 NA 2 NA 2,4,6	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recommer Pressure, Max (construction) Shoe Joint Batch Mix Circulating prior Time Between S Special Instruction	F)) nded (bpm) psi) cmtng (hr) Stages, (hr) ons 1. Do not wash 2. Wash pump: 3. Reverse out 4. Run Blend T 5. Record Rate 6. Confirm den 7. 1" cement to 8. If cement is	s and lines. Test on Cemen e, Pressure, an esitometer with e surface if cen not circulated to	60 NA 7 6 200 40 NA 0.5 NA 1,6,7 es. t d Density on 3.5" pressurized mud nent is not circula o surface, run ter	disk scales ted. np. survey	Rotate/Reciproca 4 4 2000 80 NA 1.5 NA 1,6,8	anding plug.	Rotate/Recipro 2 2 2000 40 NA 2 NA 2,4,6	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recommer Pressure, Max (construction) Shoe Joint Batch Mix Circulating prior Time Between S Special Instruction	F)) nded (bpm) psi) cmtng (hr) Stages, (hr) ons 1. Do not wash 2. Wash pump: 3. Reverse out 4. Run Blend T 5. Record Rate 6. Confirm den 7. 1" cement to 8. If cement is	s and lines. Test on Cemen e, Pressure, an esitometer with e surface if cen not circulated to	60 NA 7 6 200 40 NA 0.5 NA 1,6,7 es. t d Density on 3.5" pressurized mud nent is not circula o surface, run ter	disk scales ted. np. survey	Rotate/Reciproca 4 4 2000 80 NA 1.5 NA 1,6,8	anding plug.	Rotate/Recipro 2 2 2000 40 NA 2 NA 2,4,6	cate
Excess %, Calip BHST (est deg. Pipe Movement Rate, Max (bpm Rate Recommer Pressure, Max (shoe Joint Batch Mix Circulating prior Time Between S Special Instruction	F)) nded (bpm) psi) cmtng (hr) Stages, (hr) ons 1. Do not wash 2. Wash pump: 3. Reverse out 4. Run Blend T 5. Record Rate 6. Confirm den 7. 1" cement to 8. If cement is	s and lines. Test on Cemen e, Pressure, an esitometer with e surface if cen not circulated to	60 NA 7 6 200 40 NA 0.5 NA 1,6,7 es. t d Density on 3.5" pressurized mud nent is not circula o surface, run ter	disk scales ted. np. survey	Rotate/Reciproca 4 4 2000 80 NA 1.5 NA 1,6,8	anding plug.	Rotate/Recipro 2 2 2000 40 NA 2 NA 2,4,6	cate

Cementing Program

Slurry 1

108 sx Class G Cement

+ 2% CaCl2 (accelerator)

125 cuft

TOC@Surface

0.25 #/sk Cellophane Flake (lost circulation additive)

0.3132 cuft/ft OH 100 % excess

0.1% D46 antifoam

Slurry Properties:

Density

Yield (ft3/sk) Water

Slurry 1

(lb/gal) 15.8

1.16

(gal/sk)

4.95

Casing Equipment:

9-5/8", 8R, ST&C 1 Guide Shoe 1 Top Wooden Plug 1 Autofill insert float valve

4 Centralizers 1 Stop Ring

1 Thread Lock Compound

intermediate:

Fresh Water

20 bbl

fresh water

Lead

Slurry 1

247 sx Class "G" Cement + 3% D79 extender

TOC@Surface

+ 2% S1 Calcium Chloride

+1/4 #/sk. Cellophane Flake + 0.1% D46 antifoam'

Tail

Slurry 2

107 sx 50/50 Class "G"/Poz

+ 2% gel (extender)

135 cuft

80 % excess

717 cuft

0.1% D46 antifoam +1/4 #/sk. Cellophane Flake 0.1503 cuft/ft OH 0.1746 cuft/ft csg ann

+ 2% CaCl2 (accelerator)

Slurry Properties:

Slurry 1

Slurry 2

Density (lb/gal)

500 ft fill

11.4

Yield (ft3/sk) 2.9

1.27

Water (gal/sk) 17.77

5.72

Casing Equipment:

7", 8R, ST&C

13.5

1 Float Shoe (autofill with minimal LCM in mud) 1 Float Collar (autofill with minimal LCM in mud)

1 Stop Ring

10 Centralizers (one in middle of first joint, then every third collar)

2 Fluidmaster vane centalizers @ base of Ojo

7 Centalizers one every 4th joint from Ojo to base of surface casing

1 Top Rubber Plug

1 Thread Lock Compound

Production:

Fresh Water

10 bbl

CW100

Lead

Slurry 1

140 LiteCrete D961 / D124 / D154

+ 0.03 gps D47 antifoam

TOC@Surface

+ 0.5% D112 fluid loss

299 cuft

Cementing Program

+ 0.11% D65 TIC

1	Tail		130 sx 50/50 Class "G"	//Poz	187 cuft
5	Slurry 2		+ 5% D20 gel (exte	ender)	+ 5 #/sk D24 gilsonite
	1657 ft fill		+ 0.1% D46 antifoa	+ 0.15% D65 TIC	
			+ 1/4 #/sk. Celloph	ane Flake	+ 0.1% D800 retarder
			+ 0.25% D167 Flui	d Loss	
					0.1026 cuft/ft OH
Slurry Properties:		Density	Yield	Water	10 % excess
		(lb/gal)	(ft3/sk)	(gal/sk)	0.1169 cuft/ft csg ann
Slurry 1	•	9.5	2.14	6.38	
Slurry 2		13	1.44	6.5	Top of Mancos
		•			5373
Casing Equipment:		4-1/2", 8R, ST&C			
		1 Float Shoe (auto	fill with minimal LCM in mud)		
		1 Float Collar (auto	ofill with minimal LCM in mud)		
		1 Stop Ring			
		39 Centralizers (ev	ery third joint		
		1 Top Rubber Plug			
		1 Thread Lock Cor	npound		

Note:

- 1. The job should be pumped at 2-3 bpm max rate. Do not exceed 3 bpm on displacement
- 2. Wash pump and lines before displacement. Slow to 1 bpm for the last 30 bbl of displacement.

300451118700 4000 PRODUCTION (00) AMOCO PRODUCTION 300481117109 HOTON RES 0442 SIGNEY 2797503 CONTROL TO PROBLEM STORE PRODUCTION DO SOLD AREAS NOCE AMOUNT PRODUCTION DO SOLD AREAS NOCE AMO # RESEARCH TO BE GAS CO 2004-88150 CO 2004-8 MURLINGTON RES DAG CO COCABBBBAGGG # ANOXO PROTONICO JANOTON RES ONES CO. 8004E2473 045228500 SECASSESSED 60 MANOCO PROSUCTION CO PRODUCTION CO 30046877 AMOCO PROS 508402794006 # #4000 ##00H05!0# AMOOU PRODUCTION PO 300481197900 AMOCO PRODUCTIO BOUCTION ED 300452252700 AMOOD PRODUCTION CO

AMOOD PRODUCTION CO

SOCIETION CO

SOCIETION CO

AMOOD PRODUCTION CO

SOCIETION CO

AMOOD PRODUCTION AMOOD PRODUCTION

AMOOD PRODUCTION CO

AMOOD PRODUCTION <u>ಸ್ಥಾರವರ್ಥಿಕ ಅಭಿ</u>ಚ MARSO PREBOCTION OF 68°1968235964 co 300482471900 CQ_F9004471904 CO GREAT VESTERN SAID CO 200491067900 3004581072800 CD 3004 30047800007100 CD AMOGO P 300458107800 CD 300452231100 300458107800 SECO CD 300452231100 300482528350 AMOGO PRODUCTION SOC4ERIOTEDO AMOCO FRESSACTIO 300451084000 AMDCD PRODUCTION OF PRODUCTION co recounnes ca MANOCO PRODUCTION CO .500408275898 Ax000 PRAED1700 CO 2004 PRODUCTION CO

•	DANGTH HCTIVE NEUL
•	BREGTA INACTIVE HELL
٠	HESHVERDE RCTIVE HELL
◙	HERRYERDE INRCTIVE WELL
*	PRETELENO COME MOTTVE HELL
(*)	FANTELAND COST TORCHTS MELL
•	PICTURES CLIPPS SCTINE WELL
(*)	PITTURED CLIFFS INSCTIVE WELL

Amoco Production Company Houston, Texas
San Juan Basin
9 Section Plat 31N 11W SECTION 4 Mudge LS #22M
C. E. SACKETT DETE 18-JUN-2001