

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. 14-20-604-86
2. NAME OF OPERATOR S & B Drilling Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Ute Mountain Tribe
3. ADDRESS OF OPERATOR 158 Petroleum Center Bldg Farmington N.M.		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980 fsl 1980-REL Sec 20 T31N R15W SAN JUAN Co. New Mexico		8. FARM OR LEASE NAME SW Barker Dome
14. PERMIT NO.		9. WELL NO. 2
15. ELEVATIONS (Show whether DF, RT, GR, etc.)		10. FIELD AND POOL, OR WILDCAT Verde Gallup
		11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA Sec 20 T31N R15W NMPM
		12. COUNTY OR PARISH SAN JUAN
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☒	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☒	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is proposed to plug AND ABANDON this well in the following manner:

1. Spot 119 ft Cement plug from 1845 to 1964 to cover perf.
2. Cut off 4 1/2" Casing @ Approx 1640 & Recover Same
3. Spot 100 ft Cement plug Across Stubs from 1580 to 1680
4. Spot 100 ft Cement plug Across Surface Casing Shoe from 298 to 345
5. Ered P&A MARKER w/ 108" Surface Plug

Date of Last Production July 1962

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]
(This space for Federal or State office use)

TITLE Agent for Operator

DATE May 16, 1966

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

APPROVED

MAY 12 1966

E. A. SCHMIDT

*See Instructions on Reverse Side

