

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1650' FSL, 990' FWL, Sec. 17, T-32-N, R-6-W, NMPM, San Juan County

RECEIVED
NOV 13 1996

OIL CON. DIV.
DIST. 3

API # (assigned by OCD)

30-045-60056

5. Lease Number

Fee

6. State Oil & Gas Lease #

7. Lease Name/Unit Name

Allison Unit

8. Well No.

2

9. Pool Name or Wildcat

Blanco Mesaverde

10. Elevation:

Type of Submission

Type of Action

☐ Notice of Intent	☒ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☐ Other -	

13. Describe Proposed or Completed Operations

10-22-96 MIRU. SDON.


10-23-96 ND WH. NU BOP. TOO H w/186 jts 2 3/8" tbg. TIH w/7" gauge ring to 5630'. TOO H. TIH w/7" BP, set @ 5612'. TOO H. TIH, tag BP @ 5612'. Pump 155 bbl wtr down csg & out bradenhead. No circ. SDON.

10-24-96 Establish circ w/12 bbl wtr. Plug #1: pump 40 sx Class "B" cmt @ 5404-5612'. TOO H to 3776'. Plug #2: pump 29 sx Class "B" cmt inside csg @ 3625-3776'. TOO H. TIH, perf 3 sqz holes @ 3284'. Tag TOC on plug #2 @ 3637'. TOO H. TIH w/7" cmt retainer, set @ 3223'. PT tbg to 1000 psi, OK. Establish injection. Plug #3: pump 21 sx Class "B" cmt below cmt retainer outside 7" csg @ 3184-3284'. Pump 17 sx Class "B" cmt inside csg on top of cmt retainer, TOC @ 3135'. TOO H to 2824'. Perf 3 sqz holes @ 2885'. TOO H. TIH w/7" cmt retainer, set @ 2824'. TOO H. TIH. (Johnny Robinson w/NMOCD on location). SDON.

10-25-96 Establish injection. Plug #4: pump 21 sx Class "B" cmt outside 7" csg @ 2785-2885' below cmt retainer. Pump 17 sx Class "B" cmt inside csg on top of cmt retainer to 2736'. TOO H to 1934'. Perf 3 sqz holes @ 1972'. TOO H. TIH w/7" cmt retainer, set @ 1934'. Establish injection. Plug #5: pump 33 sx Class "B" cmt outside 7" csg @ 1872-1972' below cmt retainer. Pump 22 sx Class "B" cmt on top of cmt retainer inside csg to 1820'. TOO H. TIH, perf 3 sqz holes @ 239'. TOO H. TIH w/7" cmt retainer, set @ 184'. Pump #6: pump 75 sx Class "B" cmt below cmt retainer w/bradenhead valve open. & csg valve shut. Open csg valve pump 16 sx Class "B" cmt. Circ 1 bbl cmt to surface. SD for weekend.

10-28-96 ND BOP. Cut off WH. Install dry hole marker w/15 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 10-28-96.


SIGNATURE



Regulatory Administrator November 11, 1996

(This space for State Use)

Approved by



Title DEPUTY OIL & GAS INSPECTOR, DIST. #3

Date

NOV 13 1996