

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved
Budget Bureau No. 42-R100

RECEIVED
MAY 18 1983
FARMINGTON DISTRICT

1. ☒ gas well ☐ other

2. NAME OF OPERATOR
Amoco Production Company

3. ADDRESS OF OPERATOR
592 Airport Dr., Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1650' ~~FEL~~ x 990' ~~FEL~~
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

5. LEASE
I-22-IND-619 MAY 1 1983

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Ute Indians

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Ute Indians A

9. WELL NO.
5

10. FIELD OR WILDCAT NAME
Ute Dome Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SE/NE, Section 35, T32N, R14W

12. COUNTY OR PARISH
San Juan

13. STATE
NM

14. API NO.
30-045-11165

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6203' DF

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☒
PULL OR ALTER CASING ☒
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other)

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

JUL 25 1983

OIL CON. DIV.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Amoco Production Company requests approval to repair the above well according to the following procedure:

1. Drill out to 2520'.
 2. Run Gamma Ray, induction, and cement bond logs.
 3. Perforate 7" casing with a squeeze shot.
 4. Run 4-1/2" casing from surface to 2520', setting a DV tool at 2100' or below cement top, whichever is lower.
 5. Cement first stage with 40 sx class B, 2% CaCl₂, 4% gel cement.
 6. Circulate 2 hrs.
 7. Cement second stage w/the same type cement as above & sufficient volumes to fill 4-1/2" - 7" and 7" - open hole annullis.
 8. When cement circulates from 4-1/2" - 7" annulus, close bradenhead and squeeze remaining cement through squeeze shot behind 7" pipe.
 9. Shut down and wait on completion procedure.
- Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

Original Signed By

SIGNED D. U. TAYLOR

TITLE Dist. Admin. Supervisor

5-10-83

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY

Sharon Mieser

(This space for Federal or State office use)

TITLE for acting

DATE 5/13/83

District Supervisor

0 + 1 MMS, Grand Junction
1 - C.C. Burnside, Denver
1 - Ben

m. Partners

*See Instructions on Reverse Side