


Form 9-230



LOCATE WELL CORRECTLY

 Budget
 Approved

 Bureau No. 42-R355.1
 expires 11-30-49.
U. S. LAND OFFICE Ute IndiansSERIAL NUMBER I-22-Ind-619LEASE OR PERMIT TO PROSPECT _____
Ute Dome
 UNITED STATES
 DEPARTMENT OF THE INTERIOR
 GEOLOGICAL SURVEY

LOG OF OIL OR GAS WELL

Company Stanolind Oil & Gas Co. Address Farmington, New Mexico
 Lessor or Tract Ute Indians Field Ute Dome State New Mexico
 Well No. 4 Sec. 35 T32N R. 14W Meridian T&PM County San Juan
 Location 1980 ft. {N.} of S. Line and 660 ft. {E.} of E. Line of Sec. 35 Elevation 6150
(Denote feet relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon
 so far as can be determined from all available records.

Signed R. B. MoultonDate September 16, 1948Title Pipe Line Foreman

The summary on this page is for the condition of the well at above date.

Commenced drilling March 5, 1948 Finished drilling August 30, 1948

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from 2295 to 2522 (G) No. 4, from 8370 to 8600 (G)
 No. 2, from 4650 to 4810 (G) No. 5, from _____ to _____
 No. 3, from 7830 to 7980 (G) No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____ No. 3, from _____ to _____
 No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
13-3/8	48	8	Waco	335	None	Surface	8295	8360	Intermediate
8-5/8	32	8	S. H. Jones	2524	Baker	Intermediate	8295	8360	Production
5 1/2	17	8	New	8500	None	Production	8295	8360	Production

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
13-3/8	335	275	Halliburton		
8-5/8	2524	300	"		
5 1/2	8600	970	"		

PLUGS AND ADAPTERS

Hoisting plug—Material _____ Length _____ Depth set _____

FOLD MARK

 RECEIVED
 OCT 14 1965
 OIL CON. COM.
 DIST. 3