

(SUBMIT IN TRIPLICATE)

Indian Agency \_\_\_\_\_

UNITED STATES

Navajo Ute

DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Allottee Mountain Tribal

Lease No. 14-20-600-3540

Sec. 35	
• 75	

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<b>XX</b>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	Perforating & Treating	<b>XX</b>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 10, 1963

Well No. 5 is located 660 ft. from N line and 1900 ft. from W line of sec. 35SE 1/4 SW 1/4 Sec. 35  
(1/4 Sec. and Sec. No.)32N  
(Twp.)17W  
(Range)N.M.P.M.  
(Meridian)Undesignated Gallup  
(Field)San Juan  
(County or Subdivision)New Mexico  
(State or Territory)

RECEIVED

JUL 11 1963

The elevation of the derrick floor above sea level is 5791 ft.U. S. GEOLOGICAL SURVEY  
FARMINGTON, NEW MEXICO

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well spudded June 7, 1963. Set 7-5/8" OD casing at 20' &amp; cemented by hand. W.O.C. Drilled to 1447'.

CORE NO. 1 - 1441' - 1441' - (20') - Recovered 20'

Top - 7' - Shale  
 Next - 2' - Shale with Sand streaks  
 Next - 10' - Gray sand oil saturated  
 Next - 1' - Sandy shale

Reached total depth of 1715' on June 13, 1963. Set 4-1/2" OD casing at 1700' and cemented with 100 sacks. W.O.C. 24 hrs. Shut off tested OK. Did not drill out cement plug at 1441'. FSTD 1441'. Perforated 4-1/2" OD casing from 1690-1660' for a total of 10' and 40 holes. Treated through 4-1/2" OD casing perfor. 1690-1660' with 29,736 gallons lease oil and 30,000 20/40 sand. After recovering all lease oil well pumped 140 barrels of oil in 24 hours.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Shelly Oil CompanyAddress Box 730Hobbs, New MexicoBy (ORIGINAL) H. E. AsbTitle Dist. Supt.RECEIVED  
JUL 12 1963  
OIL CON. COM.  
DIST. 3

ORIGINAL H. E.