Form 3160-5

UNITED STATES

	NT OF THE INTERIOR LAND MANAGEMENT	Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No.
Do not use this form for proposals to di	AND REPORTS ON WELLS rill or to deepen or reentry to a different reservoir R PERMIT—" for such proposals	6. If Indian, Allottee or Tribe Name
I. Type of Well Gas	IN TRIPLICATE APR 2002	7. If Unit or CA, Agreement Designation
2. Name of Openator At the Development Corp 3. Address and Telephone No. 1000 Kee Brayos 4. Location of Well (Footage, Sec., T., R., M., or Survey D. See 35 3.2 N Aut Lette I 18	760 30 FSL 810 FEL	8. Well Name and No. 9. API Well No. 30-045-11156 10. Field and Pool, or Exploratory Area 11. County or Parish, State
TYPE OF SUBMISSION	s) TO INDICATE NATURE OF NOTICE, REPO	
Notice of Intent Subsequent Report Final Abandonment Notice	Abandonment Recompletion Plugging Back Casing Repair Altering Casing Other	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
13. Describe Proposed or Completed Operations (Clearly state a give subsurface locations and measured and true vertically state and true vertically	Ill pertinent details, and give pertinent dates, including estimated date of starcal depths for all markers and zones pertinent to this work.)*	rting any proposed work. If well is directionally drilled

PEOR RECOR

(This space for Federal or State office use)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



Key Energy Services, Inc. Four Corners Division 5651 US Highway 64 P.O. Box 900 Farmington, NM 87499

Phone: 505-327-4935 Fax: 505-327-4962

P&A OPERATION CEMENT SERVICE REPORT

WELL NAME: NAVAJO P#12

DATE STARTED: 09-20-01

DATE COMPLETED: 09-25-01

TOTAL PLUGS SET: 3

TOTAL SACKS USED: 100 SX

STATE WITNESS: H. VILLENUEVA

TRIBE WITNESS: N/A

MOL AND SPOT RIG AND PLUGGING EQUIPMENT. RU RIG, UNSEAT PUMP AND HOT OIL RODS AND TBG. NU BOP. PU AND STRAP OUT WITH 1304.15' OF 2 3/8" TBG.

PLUG #1 (820' - 1253'), RIH AND SET RETAINER AT 1253'. CIRCULATE HOLE AND ATTEMPT TO PRESSURE TEST CSG BUT INJECTED AT .5 BPM WITH 350 PSI. STUNG INTO RETAINER AND ESTABLISHED INJECTION RATE AT 0 BPM WITH 1000 PSI. STUNG OUT AND BALANCED 32 SX CL. B CEMENT PLUG INSIDE CSG. POH AND WOC. RIH AND TAG TOC AT 820'. POH.

RU WIRELINE AND PERFORATED SQUEEZE HOLES AT 80°. ATTEMPTED TO CIRCULATE TO SURFACE WITH WATER BUT DID NOT SEE ANY SIGNS OF COMMUNICATION. NMOCD APPROVED CHANGE IN PROCEDURE.

PLUG #2 (208' - 313'), BALANCED 12 SX CL. B CEMENT PLUG INSIDE CSG. POH AND WOC. RIH AND TAGGED TOC AT 208'. POH.

ATTEMPTED TO CIRCULATE TO SURFACE WITH WATER BUT DID NOT SEE SIGNS OF COMMUNICATION. NMOCD APPROVED CHANGE IN PROCEDURE.

PLUG #3 (SURFACE, 0' - 80'), PU AND SET 4 1/3" RETAINER AT 61'. PLACED 50 SX CL. B CEMENT BELOW RETAINER AND 6 SX ABOVE RETAINER TO FILL CSG WITH CEMENT. POH. NO RETURNS SEEN AT SURFACE.

RD RIG AND CUT OFF WELLHEAD AND INSTALLED DRY HOLE MARKER ON 9-25-01.

NATHAN E. CRAWFORD. P&A SUPERVISOR