



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency _____
Navajo Sta. _____
Allottee Mountain Tribal _____
Lease No. 14-28-400-3340

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	XX
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	Perforating & Treating	XX

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Navajo "P"
Well No. 9 is located 1900 ft. from [N] line and 1900 ft. from [W] line of sec. 35
S.E. 1/4 Sec. 35 (1/4 Sec. and Sec. No.) 35 (Twp.) 17N (Range) N.M.P.M. (Meridian)
Many Banks Valley (Field) San Juan (County or Subdivision) Navajo (State or Territory)

The elevation of the derrick floor above sea level is 9777 ft. 37

RECEIVED
AUG 9 1963

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

Well spudded July 14, 1963. Set 7-1/8" OD casing at 28' and cemented with 8 sacks by hand. W.O.C. Spilled to 1400'.
GAS. 1 - 1400' - 1736' (20') - REACHED 18'
Top - 3' - Sandy shale
Next - 4' - Gray sand, oil saturated
Next - 4' - Gray sand, light, partly oil saturated with horizontal fractures
Next - 9' - Shale with lime streaks
Reached total depth of 1736' on July 18, 1963. Set 4-1/2" OD casing at 1736' and cemented with 100 sacks. W.O.C. 24 hrs. Shut off tested OK. Did not drill out cement plug at 1736'. F.B.T.D. 1736'. Perforated 4-1/2" OD casing from 1400'-1494' for a total of 6' & 12 holes. Treated through 4-1/2" OD casing ports. 1400'-1494' with 40,990 gallons of lease oil and 10,000# 20/40 sand and 6 - 3/8" ball sealers.
After recovering all lease oil well pumped 120 barrels of oil in 24 hours.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Shelly Oil Company

Address Box 730

Navajo, New Mexico

By (ORIGINAL SIGNED) H. E. Aab

Title Dist. Supt.



THE
LIBRARY
OF THE
CONGRESS

UNIVERSITY OF MICHIGAN