


| | | | | | | | | | |
|----|----|----|----|----|----|----|----|----|----|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 |
| 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 |
| 31 | 32 | 33 | 34 | 35 | 36 | 37 | 38 | 39 | 40 |



SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency _____
Havajo Mts _____
Allottee Mountain Tribal _____
Lease No. 14-20-400-3540


SUNDRY NOTICES AND REPORTS ON WELLS

| | | |
|---|--|----|
| NOTICE OF INTENTION TO DRILL | SUBSEQUENT REPORT OF WATER SHUT-OFF | XX |
| NOTICE OF INTENTION TO CHANGE PLANS | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO REDRILL OR REPAIR WELL | SUBSEQUENT REPORT OF REDRILLING OR REPAIR | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | SUBSEQUENT REPORT OF ABANDONMENT | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | SUPPLEMENTARY WELL HISTORY | |
| NOTICE OF INTENTION TO ABANDON WELL | Perforating & Fracturing | XX |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Hobbs, New Mexico May 28, 1963

Havajo #P
Well No. 1 is located 1990 ft. from [N] line and 610 ft. from [W] line of sec. 35
SW/4 NW/4 Sec. 35 32-N 17-W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Undesignated Gallup San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)



The elevation of the derrick floor above sea level is 5791 ft.

U. S. GEOLOGICAL SURVEY
FEDERAL BUREAU OF MINES

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well spudded May 4, 1963. Set 8-5/8" OD casing at 19' and cemented with 17 sacks by hand. W.O.C. 24 hrs. Drilled to 1653'.

Core No. 1 - 1653' - 1673' (20') - Recovered 20'

Top - 5' - Light gray sand with good stain & odor saturated with oil throughout
Next - 15' - Shale

Reached total depth of 1705' on May 8, 1963. Set 4-1/2" OD casing at 1698' and cemented with 100 sacks. W.O.C. 24 hrs. Shut off tested OK. Did not drill out cement plug at 1692'. P.B.T.B. 1692'. Perforated 4-1/2" OD casing from 1651-1657' for a total of 6' and 24 holes. Treated through 4-1/2" OD casing perfor. 1651-1657' with 33,600 gallons of lease oil & 30,000 20/40 sand. After recovering all lease oil well pumped 190 barrels of oil in 24 hours.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Shelly Oil Company
Address Box 38
Hobbs, New Mexico
By (ORIGINAL) H. E. Aab
Title Dist. Supt.

1917

1917

1917

1917

1917

1917

1917

1917

1917

1917

1917

1917

1917

1917

1917

1917

1917

1917

1917

1917

1917