

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOG OF ~~WELL~~ ^{P & A}

LOCATE WELL CORRECTLY

1980

OIL OR GAS SANDS OR ZONES		(Denote gas by G)	
No. 1, from	None	to	No. 4, from
No. 2, from		to	No. 5, from
No. 3, from		to	No. 6, from
IMPORTANT WATER SANDS			
No. 1, from	None	to	No. 3, from
No. 2, from		to	No. 4, from

CASING RECORD

Case No.	Size and cost of pump	Threads per inch	Make	Amount	Kind of steel	Cut and pulled from	Perforated from—	To—	Notes
1	12 in. x 12 in. \$100.00	1 1/2 in.	W. & A. M.	100.00	Steel	From top of well	From top of well	From top of well	Notes

HISTORY OF OIL OR GAS WELL

MUDDING AND CEMENTING RECORD

Size casing	Weight per foot	Number sacks of cement	Method used	Kind gravel	Amount of mud used
2	24	14	Dump		None

PLUGS AND ADAPTERS

Abdomen—Material		Length		Depth and	
Heaving plug—Material					

SHOOTING RECORD

[illegible]

TOOLS USED

Rotary tools were used from	feet to	feet, and from	feet to
Cable tools were used from	feet to	feet, and from	feet to

DATE

Rock pressure lbs. per sq. in.	
It gas well, cu. ft. per 24 hours	
emulsion;% water; and% sediment.	
The production for the first 24 hours was 188A barrels of fluid of which% was oil;%	
Put to producing	P & A
October 13, 1964	10

EMPLOYEES

Driller	La Plata Drilling Corp., Driller
Driller	Driller

FORMATION RECORD

FROM	TO	TOTAL FEET	FORMATION
1844	1952 TD	81	Juan Lopez
1952	1844	119	Niobara
308	1952	1412	Mancos
Surface	308	308	Mesa Verde

P & A RECORD

1750	0021	1601	W/30 ax cement
350	1001	1601	W/30 ax cement
Surface	421	401	W/10 ax cement

FORMATION

FORMATION RECORD—Continued