

## MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Alamosa Formation Alamosa County San Juan  
Initial 11 Annual \_\_\_\_\_ Special \_\_\_\_\_ Date of Test 10/3/59  
Company Antec Oil and Gas Company Lease Alamosa Well No. 13  
Unit 11 Sec. 20 Twp. 32N Rge. 12E Purchaser \_\_\_\_\_  
Casing 7 Wt. 20-21 I.D. 6.75 Set at 1700 Perf. 1600 To 1700  
Tubing 8 Wt. 14.7 I.D. 1.645 Set at 1702 Perf. 1755 To 1701  
Gas Pay: From 1600 To 1700 L \_\_\_\_\_ xG \_\_\_\_\_ -GL \_\_\_\_\_ Bar.Press. \_\_\_\_\_  
Producing Thru: Casing \_\_\_\_\_ Tubing X Type Well \_\_\_\_\_  
Date of Completion: 10/3/59 Packer \_\_\_\_\_ Single-Bradenhead-G. G. or G.O. Dual  
Reservoir Temp. \_\_\_\_\_

## OBSERVED DATA

Tested Through (Prover) (Choke) (Manometer) Type Taps \_\_\_\_\_

Flow Data						Tubing Data		Casing Data		Duration of Flow Hr.
No.	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h <sub>w</sub>	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
1.		.750	1.2			1.2	65	7.0		11.45
2.										1.00
3.										
4.										
5.										

## FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wpf}}$	Pressure psia	Flow Temp. Factor F <sub>t</sub>	Gravity Factor F <sub>g</sub>	Compress. Factor F <sub>pv</sub>	Rate of Flow Q-MCFPD @ 15.025 psia
1.	12.2650		159	.9952	.9003	1.035	1.301
2.							
3.							
4.							
5.							

## PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio \_\_\_\_\_ cf/bbl.  
Gravity of Liquid Hydrocarbons \_\_\_\_\_ deg.  
P<sub>c</sub> \_\_\_\_\_ (1-e<sup>-s</sup>)

Specific Gravity Separator Gas \_\_\_\_\_  
Specific Gravity Flowing Fluid \_\_\_\_\_  
P<sub>c</sub> 1000 P<sub>c</sub> 1,110

No.	P <sub>w</sub> P <sub>t</sub> (psia)	P <sub>t</sub> <sup>2</sup>	F <sub>c</sub> Q	(F <sub>c</sub> Q) <sup>2</sup>	(F <sub>c</sub> Q) <sup>2</sup> (1-e <sup>-s</sup> )	P <sub>w</sub> <sup>2</sup>	P <sub>c</sub> <sup>2</sup> -P <sub>w</sub> <sup>2</sup>	Cal. P <sub>w</sub>	P <sub>w</sub> P <sub>c</sub>
1.	791					627,241	182,100		
2.									
3.									
4.									
5.									

Absolute Potential: 1,110 MCFPD; n .75

COMPANY Antec Oil and Gas Company  
ADDRESS Box # 724, Farmington, New Mexico  
AGENT and TITLE ORIGINAL SIGNED BY D. E. BRYANT  
WITNESSED \_\_\_\_\_  
COMPANY \_\_\_\_\_

REMARKS



## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

$Q$  = Actual rate of flow at end of flow period at W. H. working pressure ( $P_w$ ).  
MCF/da. @ 15.025 psia and 60° F.

$P_c$  = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.  
psia

$P_w$  = Static wellhead working pressure as determined at the end of flow period.  
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

$P_t$  = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

$P_f$  = Meter pressure, psia.

$h_w$  = Differential meter pressure, inches water.

$F_g$  = Gravity correction factor.

$F_t$  = Flowing temperature correction factor.

$F_{pv}$  = Supercompressability factor.

$n$  = Slope of back pressure curve.

Note: If  $P_w$  cannot be taken because of manner of completion or condition of well, then  $P_w$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_t$ .

OIL COMMISSION		
DISTRICT OFFICE		
Well No.	NO.	
Well Name	DATE	
Location		
State Land Office		
U. S. G. S.		
Transporter		
File		