

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Sundry Notices and Reports on Wells

1. Type of Well
Oil
2. Name of Operator
Harrison Pet.
Texas Pacific Oil & Gas Co., C/O Joseph E. Seagram & Sons, Inc.
3. Address & Phone No. of Operator
800 3rd Ave., New York City, NY 10022-7699
4. Location of Well, Footage, Sec., T, R, M
660' FSL and 660' FEL, Sec. 27, T-32-N, R-17-W, NMPM
5. Lease Number
14-20-603-5012
6. If Indian, All. or
Tribe Name
Navajo
7. Unit Agreement Name
N/A
8. Well Name & Number
Navajo #4
9. API Well No.
30-045-1123400
10. Field and Pool
Many Rocks
11. County & State
San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

Texas Pacific Oil & Gas Co., plugged and abandoned this well on March 25, 1997,
per the attached Plug & Abandonment report.

RECEIVED
APR - 8 1997

OIL CON. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct.

Signed

William F. Clark

Title

Contractor

Date 4/2/97

William F. Clark, President A-Plus Well Service

(This space for Federal or State Office use)

APPROVED BY

[Signature]

Title

Pet Engineer

Date

APR 3 1997

CONDITION OF APPROVAL, if any:

A - PLUS WELL SERVICE, INC.

P.O. BOX 1979
FARMINGTON, NM 87499
505-325-2627 • FAX: 505-325-1211

Texas Pacific Oil & Gas Co.,
c/o Joseph E. Seagram & Sons

Navajo #4

660' FSL and 660' FEL Sec.27 , T-32-N, R-17-W,
San Juan County, NM
BIA 14-20-603-5012

APR 2 1997

Plug & Abandonment Report

Cementing Summary:

Plug #1 with 50 sxs Class B cement from 1773' to 1126' to fill Gallup perforations and cover top.

Plug #2 with 101 sxs Class B cement pumped down 4-1/2" casing from 378' to surface, cover Mesaverde top and circulate good cement to surface.

Plugging Summary:

Notified BLM on 3/21/97

- 3-21-97 Safety Meeting. Road rig to location. Spot rig and move pump jack. SDFD.
- 3-24-97 Safety Meeting. RU rig and equipment. Open up well, no pressures. PU on rods and unseat pump. RU Mote Hot Oil Truck. Hot oil 30 bbls down tubing and out casing. RD Mote. POH and LD 70 5-8" rods, 2' sub and pump. Break wellhead cap loose and PU on tubing; free. Install wellhead and BOP. PU 1 joint tubing and RIH; tag bottom at 1781'. POH and LD 1 joint tubing. Plug #1 with 50 sxs Class B cement from 1773' to 1126' to fill Gallup perforations and cover top. POH and LD tubing. Shut in well and WOC. SDFD.
- 3-25-97 Safety Meeting. Open up well, no pressures. Load casing with 8 bbls water and pressure test to 300#; held OK. RU A-Plus wireline truck and RIH; tag cement at 1078'. RIH and perforate 3 squeeze holes at 378'. Establish circulation down 4-1/2" casing and out 8-5/8" bradenhead annulus with 10 bbls water. Plug #2 with 101 sxs Class B cement pumped down 4-1/2" casing from 378' to surface, cover Mesaverde top and circulate good cement to surface. Shut in well and WOC. Dig out wellhead. ND BOP. Break off wellhead. Cut wellhead off and found cement down 10 in 4-1/2" casing and 8-5/8" annulus. Mix 15 sxs Class B cement and install P&A marker. RD rig and equipment; move off location.
- J. Sanchez, BLM representative was on location.