

(SUBMIT IN TRIPLICATE)


Indian Agency Navajo

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

14-20-603-592

Allottee \_\_\_\_\_

Co. Lease No. 221461



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Subsequent report of DST</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

HUMBLE & CONTINENTAL OIL CO.  
NAVAJO TRIBE OF INDIANS "B"

Farmington, N.M., September 26, 1956

Well No. 2 is located 1650 ft. from NI line and 1650 ft. from EW line of sec. 29

NW/4 SE/4 Section 29 T-12-N R-20-W \_\_\_\_\_  
(34 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Four Corners Paradox San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 4920 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

9/21/56: DST #3 5758 to 5769 w/1" top & 3/4" bottom chokes. Tool open 2 hrs. Weak blow for 6 min, fair blow for remainder of test. Recovered 15' slightly oil cut mud. Initial mud 3025#, Min. & Max. Fl. 70#, final 3015#. SI after 1 hr. Chloride in test 5000 PPM, in ditch 500 PPM.

9/26/56: DST #4 5801 to 5867 w/1" top & 3/4" bottom chokes. Tool open 1 hr. Weak blow for 15 min. & then died. Recovered 10' drilling mud, N.S. Initial mud 2745#, Min. & Max. Fl. 0#, final 2745#. BU after 30 min. 0#. Chloride in test 500 PPM, in ditch 500 PPM, Test satisfactory.

9/26/56: DST #5 5860 to 5917 w/1" top & bottom chokes. Tool open 45 min. Weak blow for 15 min. then died. Recovered 10' drilling mud, Initial mud 3070#, min. & max fl. 31#, final 3070# BU after SI 30 min. 31#. Chloride in test 500 PPM, in ditch 500#. Test satisfactory.

I understand that this plan of work must receive approval in writing by the Geological Survey before operation may be commenced.

Company Humble Oil & Refining Company

Address Box 1268

Farmington, New Mexico

By Russell W. Lilly  
Title District Superintendent

