

APPROVED

Form 9-3815

(April 1952) (Orig. Sgd.) J. W. LONG

(SUBMIT IN TRIPLICATE)

Budget Bureau No. 42-R339.4
Approval expires 12-31-60.Indian Agency San JuanContract 14-02-472-722Allottee Tract 17

Lease No. _____

ACTING DISTRICT ENGINEER	

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED

MAY 3 1956

GEOLOGICAL SURVEY
SAN JUAN, NEW MEXICO

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Subsequent Reported Pumping & Acidizing</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

NAME OF FIELD OFFICE

Farmington, New Mexico, April 12, 1956

Well No. 2 is located 1900 ft. from [S] line and 640 ft. from [W] line of sec. 29

1/4 of 1/4 of Sec. 29

30-2

20-2

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

Four Corners Area W/O

San Juan

New Mexico

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is 4034 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

4/9/56 On five hour combing test produced no water, oil or gas.

4/10/56 Set Baker GI bridge plug at 4300'. Pumped 2 sacks cement on top of plug. Set Baker GI bridge plug at 4300'. Perforated 1 1/2" cas. w/ 200 gals. jet shots per ft. from 3972'-3992'.

4/11/56 Ran tubing w/ 1000 packer set at 3990' and tubing at 3992'.

4/12/56 Cased well down. Filled well case on hour for 3 hrs, recovering small amount of gas each pull. Washed perforations from 3972' to 3992' w/ 200 gals. Densil and acid. 20 pr. 2000#. Soaks to 2500#. Ave. injection rate .8 bbls./min @ 2400#.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be started.

Company Humble Oil & Refining CompanyAddress Box 1246Farmington, New MexicoBy J. E. [Signature]Title Dist. En. [Signature]

