submitted in lieu of Form 3160-5

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT Sunday Notices and Reports on Wells



	Sundry Notices and Reports	OII AAGII2		1
			5.	Lease Number 14-20-603-5012
4	Type of Well		6.	If Indian, All. or
1.	Type of Well		0.	Tribe Name
	Oil			Navajo
	Hohring Celhalon		7.	Unit Agreement Name
	No of Operator		٠.	N/A
2.	Name of Operator	Inc		14/73
	Texas Pacific Oil & Gas Co., C/O Joseph E. Seagram & Sons,	IIIO.	8.	Well Name & Number
			Ο.	* * * * * * * * * * * * * * * * * * * *
3.	Address & Phone No. of Operator		_	Navajo #7-
	800 3 rd Ave., New York City, NY 10022-7699		9.	API Well No.
				30-045-1125400
4.	Location of Well, Footage, Sec., T, R, M		10.	Field and Pool
	1850' FSL and 990' FEL Sec.27 , T-32-N, R-17-W, NMPM			Many Rocks 601
	L		11.	County & State
				San Juan County, NM
		ATIAN		D D 1 T 1
12.	CHECK APPROPRIATE BOX TO INDICATE NATURE OF N	OTICE, REPORT, O	THE	RDATA
	Type of Submission Type of Action			
		Change of Plans		
		New Construction		
		Non-Routine Fracture	ng	
	Casing Repair	Water Shut off		
	Final Abandonment Altering Casing	Conversion to Injection	วท	
	Other -			
	Describe Proposed or Completed Operations			
	•			
	Texas Pacific Oil & Gas Co., plugged and abando	ned this well on M	arch	i"17, 1997 per the
	attached Plug & Abandonment report.			
	attached Flug & Abandon Hone Topola			
		DEME	775	
		一四色ほぼ	Wi	₹ {\\}
		IN		- W
		M APR - 4 1	997	D
	I I are his and if a the foregoing is true and correct	OIL CON	0	11.47
14.	I hereby certify that the foregoing is true and correct.			a we
	ned William F Clar Title C	Contractor DIST.	ક	Date3/24/97
Sig	100	Contractor		Date0/24/01
	William F. Clark, President A-Plus Well Service			
	(E t l Olde Office cost	2		APR 02 1903
	s space for Federal or State Office use)	79		Data .
	PROVED BY TITLE (Mengine	4	Ualc
	ADITION OF APPROVAL if any:	~		

A - PLUS WELL SERVICE, INC.

P.O. BOX 1979 FARMINGTON, NM 87499 505-325-2627 • FAX: 505-325-1211

Texas Pacific Oil & Gas Co., c/o Joseph E. Seagram & Sons Navajo #7-27 Well 1850' FSL and 990' FEL Sec.27, T-32-N, R-17-W, San Juan County, NM BIA 14-20-603-5012

March 24, 1997

Plug & Abandonment Report

Cementing Summary:

Plug #1 with 43 sxs Class B cement from 1267' to 710' to fill Gallup perforations and cover top.

Plug #2 with 50 sxs Class B cement pumped down 4-1/2" casing from 84' to surface, circulate good cement to surface.

Plugging Summary:

Notified BLM on 3/14/97

- 3-14-97 Road rig to location. RU rig and equipment. Open up well, no pressure. Install wellhead. NU BOP and test, OK. PU and RIH with 42 joints 2-3/8" tubing, tag bottom at 1281'. PU tubing to 1267'. Establish circulation with 3 bbls water. Plug #1 with 43 sxs Class B cement from 1267' to 710' to fill Gallup perforations and cover top. POH and LD tubing. Shut in well and WOC overnight. SDFD.
- 3-17-97 Safety Meeting. Open up well, no pressure. Pressure test casing to 300# for 10 min, held OK. RU A-Plus wireline truck and RIH; tag cement at 759'. Perforate 2 squeeze holes at 84'. Establish circulation out bradenhead with 10 bbls water. Plug #2 with 50 sxs Class B cement pumped down 4-1/2" casing from 84' to surface, circulate good cement to surface. Shut in well and WOC. Dig out wellhead. ND BOP. Cut wellhead off; found cement down 5' in 4-1/2" casing and 7-5/8" annulus. Mix 15 sxs Class B cement, fill casing and annulus; then install P&A marker. RD rig and equipment; move off location.

 J. Sanchez, BLM representative was on location.