

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Sundry Notices and Reports on Wells

57 FEB 25 AM 7:57 5.

070 BLM, NM

1. Type of Well
Oil

2. Name of Operator

Texas Pacific Oil & Gas Co., C/O Joseph E. Seagrams & Sons, Inc.

3. Address & Phone No. of Operator

800 3rd Ave., New York City, NY 10022-7699

4. Location of Well, Footage, Sec., T, R, M

1980' FSL and 1980' FWL Sec.27, T-32-N, R-17-W, NMPM

K

Lease Number
14-20-603-5012

6. If Indian, All. or
Tribe Name

Navajo

7. Unit Agreement Name
N/A

8. Well Name & Number
Navajo #6-~~2~~

9. API Well No.
30-045-1125500

10. Field and Pool
Many Rocks

11. County & State
San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☒ Notice of Intent

☒ Abandonment

☐ Change of Plans

☐ Recompletion

☐ New Construction

☐ Subsequent Report

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Final Abandonment

☐ Altering Casing

☐ Conversion to Injection

☐ Other -

13. Describe Proposed or Completed Operations

Texas Pacific Oil and Gas Co., proposes to Plug and Abandon this well per the attached procedure and diagram.

RECEIVED
MAR - 3 1997

070 BLM, NM

14. I hereby certify that the foregoing is true and correct.

Signed William F. Clark
William F. Clark, A-Plus Well Service

Title Contractor

Date 2/24/97

(This space for Federal or State Office use)

APPROVED BY /S/ Duane W. Spencer Title _____

Date FEB 27 1997

CONDITION OF APPROVAL, if any:

Navajo #6-27

Proposed P&A

Many Rocks Gallup

1980'S, 1980'W Sec 27, T-32-N, R-17-W, San Juan County, NM

Today's Date: 2/20/97

Spud: 8/15/63

Completed: 5/31/63

Mancos @ Surface

Gallup @ 946'

Sanostee @ 1280'

6-3/4" Hole

TD 1319'

7-5/8" Casing Set @ 32'
Cmt with 10 sxs (Circulated to Surface)

Perforate at 82'

Plug #2 82' - Surface
Cmt with 17 sxs Class B.

TOC @ 945' (Calc, 100%)

TOC @ 1035' (Calc, 75%)

Plug #1 1305' - 896'
Cmt with 48 sxs Class B
(50% excess, long plug)

Gallup Perforations:
1254' - 1260'

4-1/2" Casing Set @ 1305'
Cemented with 35 sxs (50 cf)

Well History:

7-5/8" Surface Casing set at 32' cemented to surface

4-1/2" Casing set at 1305' with 35 sxs cement with 12.5# gilsonite (assumed).

Gallup zone perforated 1254' - 1260' with 4 SPF .

Converted to water disposal well in April 1965.

Reported to have pressure tested casing to 1000# in May 1992.

Proposed Plugging Procedure:

1. Release packer if present. POH with tubing. RIH and tag bottom. Plug #1 from 1305' to 896' with 48 sxs Class B cement. POH with tubing.
2. WOC and then RIH and tag cement. Pressure test casing to 300#.
3. Perforate 2 squeeze holes at 82'. Establish circulation out bradenhead. Mix and pump 17 sxs Class B cement from 82' to surface, circulate good cement out bradenhead.
4. WOC then cut off wellhead and install P&A marker.