

submitted in lieu of Form 3160-5

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
Sundry Notices and Reports on Wells

- |   |  |
|---|--|
| 1. Type of Well<br>Oil  | 5. Lease Number<br>14-20-603-5012                |
| 2. Name of Operator<br><u>Harrison Petroleum</u><br>Texas Pacific Oil & Gas Co., C/O Joseph E. Seagram & Sons, Inc. | 6. If Indian, All. or<br>Tribe Name<br>Navajo    |
| 3. Address & Phone No. of Operator<br>800 3 <sup>rd</sup> Ave., New York City, NY 10022-7699                        | 7. Unit Agreement Name<br>N/A                    |
| 4. Location of Well, Footage, Sec., T, R, M<br>1980' FSL and 1980' FWL Sec. 27, T-32-N, R-17-W, NMPM<br><u>K</u>    | 8. Well Name & Number<br>Navajo #6- <del>2</del> |
|   | 9. API Well No.<br>30-045-1125500                |
|   | 10. Field and Pool<br>Many Rocks                 |
|   | 11. County & State<br>San Juan County, NM        |

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

Texas Pacific Oil & Gas Co., plugged and abandoned this well on March 14, 1997 per the attached Plug & Abandonment report.

RECEIVED  
APR - 4 1997

OIL CON. DIV.  
DIST. 3

14. I hereby certify that the foregoing is true and correct.

Signed

William F. Clark  
William F. Clark, President A-Plus Well Service

Title

Contractor

Date 3/24/97

(This space for Federal or State Office use)

APPROVED BY

[Signature]

Title

Pet Engineer

Date

APR 02 1997

CONDITION OF APPROVAL, if any:

NMOCD

# **A - PLUS WELL SERVICE, INC.**

P.O. BOX 1979  
FARMINGTON, NM 87499  
505-325-2627 • FAX: 505-325-1211

Texas Pacific Oil & Gas Co.,  
c/o Joseph E. Seagram & Sons

March 24, 1997

## **Navajo #6-27 Well**

1980' FSL and 1980' FWL Sec.27 , T-32-N, R-17-W,  
San Juan County, NM  
BIA 14-20-603-5012

## **Plug & Abandonment Report**

### **Cementing Summary:**

Plug #1 with 42 sxs Class B cement with 2%  $\text{CaCl}_2$  from 1236' to 692' to fill Gallup perforations and cover top.

Plug #2 with 40 sxs Class B cement pumped down 4-1/2" casing from 82' to surface, circulate good cement to surface.

### **Plugging Summary:**

Notified BLM on 3/12/97

- 3-13-97 Road rig to location. RU rig and equipment. Open up well, no pressure. Install 4-1/2" x 8-5/8" wellhead. NU BOP and test. RU rig floor. PU 40 joints 2-3/8" tubing and RIH; tag bottom at 1242'. PU tubing to 1236'. Pump 1 bbl water down tubing and circulate oil out casing. Wait on water truck and pit. Procedure change approved S. Mason, BLM. Plug #1 with 42 sxs Class B cement with 2%  $\text{CaCl}_2$  from 1236' to 692' to fill Gallup perforations and cover top. POH and LD tubing. Shut in well and WOC cement. Pressure test casing to 300#, held OK. RU A-Plus wireline truck and RIH; tag cement at 753'. Perforate 2 squeeze holes at 82'. Establish circulation down 4-1/2" casing and out 7-5/8" with 4 bbls water. Plug #2 with 40 sxs Class B cement pumped down 4-1/2" casing from 82' to surface, circulate good cement to surface. Shut in well and WOC overnight. SDFD.
- 3-14-97 Safety Meeting. Open up well, no pressure. ND BOP and break off 4-1/2" wellhead. Cut wellhead off; found cement down 10' in 4-1/2" casing and 7-5/8" annulus. Mix 25 sxs Class B cement, fill casing and annulus then install P&A marker. RD rig and equipment; move off location. J. Sanchez, BLM representative was on location.