

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency _____
Window Rock _____
Allottee Hawa Jo
Lease No. 14-30-400-3540

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<u>Perforating & Treating</u>	<u>XX</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 29, 19 63

Hawa Jo "P"
Well No. 10 is located 1900 ft. from IX line and 440 ft. from W line of sec. 26
NE/4 SE/4 Sec. 26 30N 17W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Mary Esther Collins San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 9900 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well spudded July 29, 1963. Set 7-5/8" OD casing at 28' and cemented with 5 sacks of sand. W.O.C. 24 hrs. Drilled to 1771'.

COSE NO. 1 - 1771-1791' (20') - Perforated 18'4"

Top 3'4" - Medium grained glauconitic sandstone, slight clay, thin shale laminations, scattered stain and partings.

Next 2'4" - Black shale

Next 12'4" - Black shale with limestone streaks

Reached total depth of 1835' on August 1, 1963. Set 4-1/2" OD casing at 1829' and cemented with 100 sacks. W.O.C. 24 hrs. Shut off tested OK. Did not drill out cement plug at 1810'. PROD 1810'. Perforated 4-1/2" OD casing from 1764-1769' for a total of 5 feet and 20 holes. Treated through 4-1/2" OD casing ports, 1764-1769' with 44,470 gallons of lease oil and 90,000 20/40 sand.

After recovering all lease oil well pumped 44 barrels of oil in 24 hours.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Shelly Oil Company
Address Box 720
Hobbs, New Mexico

By (ORIGINAL SIGNED) H. Ash
Title Dist. Supt.

