

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

14-20-603-3519

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo-Ute Mountain

7. UNIT AGREEMENT NAME

\*\*\*\*\*

8. FARM OR LEASE NAME

Navajo-Ute Mountain

9. WELL NO.

332-26

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SW NE Sec. 26,  
T32N, R17W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole

2. NAME OF OPERATOR

The Superior Oil Company

3. ADDRESS OF OPERATOR

P. O. Drawer 'G', Cortez, Colorado

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* See also space 17 below.)

At surface

1975' from East Line & 2262' from North line,  
Section 26

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5807' G4, 5819' R.B.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Air drilled a 6-3/4" hole to 1797' T.D. with 8-5/8" casing set at 40'.

Propose to plug and abandon this well as follows:

- 1) Place 25 sacks regular cement in the bottom of the hole.  
Calculated fill up 1685'. (Log top: Sanastee-Low Gallup at 1744')
- 2) Fill hole with water.
- 3) Place 10 sacks regular cement in top of 8-5/8" casing.

Note: Above program verbally approved by Mr. P. T. McGrath by phone on 9-26-64.

18. I hereby certify that the foregoing is true and correct

J. C. GORDY

SIGNED

J. C. Gordy

TITLE

Drilling Engineer

DATE

9-30-64

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JCG/ajh

\*See Instructions on Reverse Side