

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. ☐ gas well ☒ oil well ☐ other

2. NAME OF OPERATOR
J. Gregory Merrion & Robert L. Bayless

3. ADDRESS OF OPERATOR
P.O. Box 507, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1685' FSL & 3335' FEL

AT TOP PROD. INTERVAL: same

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	☐	☐
FRACTURE TREAT	☐	☐
SHOOT OR ACIDIZE	☐	☒
REPAIR WELL	☐	☐
PULL OR ALTER CASING	☐	☐
MULTIPLE COMPLETE	☐	☐
CHANGE ZONES	☐	☐
ABANDON*	☐	☐
(other) Run 4-1/2" casing liner		☒

5. LEASE MOO-C-1420-1706	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME Ute Mountain Tribe	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME Ute	
9. WELL NO. 17	
10. FIELD OR WILDCAT NAME Barker Creek Paradox	
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA Section 19, T32N, R14W	
12. COUNTY OR PARISH San Juan	13. STATE New Mexico
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 6526 GL 6536 KB	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-02-79 Set Baker Model FA Packer at 5400'.
11-03-79 Ran Baker Model FA seal assembly on 4-1/2" log as follows:
670.67 4-1/2", 10.5#, K-55 seamless
1984.15 4-1/2", 9.5#, K-55 seamless
2735.08 4-1/2", 10.5#, K-55 seamless
Set casing in FA packer at 5400'.
11-05-79 Installed tubing spool and BOP. Ran 2" tubing with Model R packer and tested 4-1/2" casing to 3500 psi from 5395' to surface, held ok.
11-06-79 Perforated 8389-8404 with 2 jet shots/ft. Acidized perfs 8374-8404 with 5000 gal. 15% HCL with iron stabilizer.
11-07-79 Knock out expendable plug from Model D packer at 8788'. Swab test intervals 8874-8904 and 8374-8404. (con't. on back)


Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED J. Gregory Merrion TITLE Co-Owner DATE November 16, 1979

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:



General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State officials. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of, parting of, any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

[illegible]