

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office **Santa Fe**

Lease No. **SP 078137**  
Unit **SE 1/4 SW 1/4 Sec. 20,**  
**T-32N, R-13W, San Juan**  
**City, New Mexico**


**SUNDRY NOTICES AND REPORTS ON WELLS**

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL..... <b>XX</b>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 18, 1961

Well No. **1 Johns** is located **660** ft. from **[N]** line and **1580** ft. from **[W]** line of **sec. 20**  
**SE SW Sec. 20** **32-N,** **13-W** **N.M.P.M.**  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
**Undes. 0-5000 San Juan** **San Juan** **New Mexico**  
(Field) (County or Subdivision) (State or Territory)



The elevation of the derrick floor above sea level is **---** ft.

**DETAILS OF WORK**

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

*Revised Per Request*  
T.D. 2711, well was drilled to T.D. of 3426 to test Dakota. Tested H<sub>2</sub>O. Plugged Dakota with 60 sacks from 3056-3365. Set Plug at 2720 and Cal Seal 2704-2720. Well is capable of approx. 1 barrel oil per day. Plugging due to fact that the well can not be produced economically.

We Propose To:

1. Set cement plug in 5 1/2" liner over perms. 2533-2655'.
2. Cut off 7" casing at lowest free point and pull casing. Spot cement plug from 50 ft. inside 7" stub to 50 ft. above 7" stub with approx. 40 sacks cement.
3. Fill open hole with mud to surface.
4. Set 10 sacks cement plug in top of surface. Erect regulation marker and permanently abandon well.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **SOUTHERN UNION PRODUCTION COMPANY**

Address **P. O. Box 808**

**Farmington, New Mexico**

By

**L. S. Muennink**

Title

**Production Superintendent**