



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Indian Agency Navajo  
Allottee Tribal  
Lease No. 14-28-403-283

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 4, 1963

Navajo "AA"  
Well No. 10 is located 1640 ft. from S line and 1630 ft. from W line of sec. 17  
NE/4 SW/4 Sec. 17 12N 17W  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Wilcox San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the Ground ~~Surface~~ above sea level is 5479 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 10-24-63, set 7", 200, J-55 surface casing @ 13.80', cemented with 6 sacks plus 21 CuCl. Set core #1 @ 1635-1702', cut & recovered 17'. Ramped core hole, drld. to 1744' TD, ran logs, ran 3/4 jts of 4 1/2", 9.30, J-55 casing set @ 1740', cemented w/73 sacks plus 21 CuCl. Plan to notch most permeable section and sand frac w/40,000 sand & approximately 1,000 barrels of oil.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Murphy Corporation  
Address 200 Jefferson Avenue  
El Dorado  
Arkansas  
By L. L. Duncan  
Title Prod. Supt. - Direct Operations

