Form 9-331 b (April 1952)



(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency
Tribal Allottee
14-20-603-58

NOTICE OF INTENTION TO DRILL		
NOTICE OF INTENTION TO CHANGE PLANS.	i li	
	[1]	HOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SH		REDRILLING OR REPAIR
NOTICE OF INTENTION TO REDRILL OR RE		_
NOTICE OF INTENTION TO SHOOT OR ACID NOTICE OF INTENTION TO PULL OR ALTER	1 1	
NOTICE OF INTENTION TO ABANDON WELL		
MOTICE OF INTENTION TO ABANDON HELL		
(INDICATE ABO	OVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR	OTHER DATA)
	Septembe	19.63
Havajo "AA"	,1720	ft. from $\left \stackrel{E}{W} \right $ line of sec
'ell No is located	1	Tt. Irom W inte or sec.
	766	
(14 Sec. and Sec. No.)	(Twp.) (Range) (Mer	How Mexico
(Field)	(County or Subdivision)	(State or Territors) E G E V E
	· ·	UD I
he elevation of the derrick floo	or above sea level isft.	SEP 23 1963
		3EF 20 1000
	DETAILS OF WORK	HE PENINCIPAL SUPVEY
tate names of and expected depths to obje	ective sands; show sizes, weights, and lengths of propo-	ed casings; indicate mudling iGEOLOGICAL SURVEY FAFMINGTON, NEW MEXICO
		(MCROROLL III
letched w/jet-notch gun	@ 1664' & 1666'. Fractured wi	th 20,0000 of 10-20 sand,
10,000f of 20-40 send an presente 2500f, mattenn land concentration verto	d 1006 barrels of oil. AMP 24 Injection pressure 35000, aver	1909, minimum injection
10,000f of 20-40 send an presence 2500f, maximum land concentration verte	d 1006 barrels of oil. MP 21 injection pressure 35000, even	1906, minimum injection rege injection rate 37.8 RM.
10,000f of 20-40 send an presence 2500f, maximum land concentration verte	d 1006 barrels of oil. MP 21 injection pressure 35000, even	1906, minimum injection rage injection rate 37.8 MM. LP - 19006, 30 minute SIP -
10,000f of 20-40 cand an prosoure 2500f, maximum	d 1006 barrels of oil. MP 21 injection pressure 35000, even	1906, minimum injection rege injection rate 37.8 RM.
10,000f of 20-40 send en Presente 2500f, meximum land concentration verte 1120f.	i 1006 berrels of oil. MP 26 injection pressure 35000, aver is from W/gal to 110/gal. ISI	SSOF, minimum injection rego injection rate 37.8 MM. IP - 13000, 30 minute SIP - SEP 2 4 1963 OIL CON. COM.
10,000f of 20-40 send en tresoure 2500f, meximum land concentration verte 1120f.	d 1006 barrels of oil. MP 21 injection pressure 35000, even	SSOF, minimum injection rego injection rate 37.8 MM. IP - 13000, 30 minute SIP - SEP 2 4 1963 OIL CON. COM.
I understand that this plan of work must have plan as well as the standard for the largety Gorpora	i 1006 berrels of oil. MP 26 injection pressure 35000, aver is from W/gal to 110/gal. ISI	SSOF, minimum injection rego injection rate 37.8 MM. IP - 13000, 30 minute SIP - SEP 2 4 1963 OIL CON. COM.
Tunderstand that this plan of work must be supply Company 200 Jeffersen	i 1006 berrels of oil. MP 26 injection pressure 35000, aver is from W/gal to 110/gal. ISI	SSF, minimum injection rego injection rate 37.8 MM. IP - 13000, 30 winete SIP - SEP 2 4 1963 OIL CON. COM.
I understand that this plan of work must have plan as well as the standard for the largety Gorpora	i 1006 berrels of oil. MP 26 injection pressure 35000, aver is from W/gal to 110/gal. ISI	SSF, minimum injection rego injection rate 37.8 MM. IP - 1360, 30 minute SIP - SEP 2 4 1963 OIL CON. COM.
I understand that this plan of work must be supply Company	i 1006 berrels of oil. MP 26 injection pressure 35000, aver is from W/gal to 110/gal. ISI	SSOF, minimum injection rego injection rate 37.8 MM. IP - 13000, 30 minute SIP - SEP 2 4 1963 OIL CON. COM.