

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Sundry Notices and Reports on Wells

SEP 11 1997

1. **Type of Well**
Oil

2. **Name of Operator**
21st Century Investment Corp.

3. **Address & Phone No. of Operator**
C/O Walsh Engineering & Production Corp.
7415 East Main, Farmington, NM 87402 505-327-4892

4. **Location of Well, Footage, Sec., T, R, M**
1720' FSL & 460' FWL, Sec. 17, T32N, R17W

5. **Lease Number**
14-20-603-585

6. **If Indian, All. or Tribe Name**
Navajo

7. **Unit Agreement Name**
N/A

8. **Well Name & Number**
Navajo AA #7

9. **API Well No.**
30-045-11442

10. **Field and Pool**
North Many Rocks Gallup

11. **County & State**
San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

21st Century Investment Corp. plugged and abandoned this well on August 21, 1997 per the attached P&A report.

RECEIVED
SEP 15 1997

OIL CON. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct.

Signed John C. Thompson Title Agent Date 8/28/1997

(This space for Federal or State Office use)

APPROVED BY IS/ Duane W. Spence Title Date SEP 12 1997
CONDITION OF APPROVAL, if any:

NMOC

A - PLUS WELL SERVICE, INC.

P.O. BOX 1979
FARMINGTON, NM 87499
505-325-2627 • FAX: 505-325-1211

Well file

August 28, 1997

21st Century Investment Corp.
c/o Walsh Engineering & Production Corp.
Navajo AA #7
1720' FSL and 460' FWL Sec.17, T-32-N, R-17-W,
San Juan County, NM
BIA 14-20-603-505

Plug & Abandonment Report**Cementing Summary:**

Plug #1 with retainer at 1554', mix 47 sxs Class B cement; squeeze 24 sxs below retainer to fill Gallup perforations and leave 23 sxs above to cover top.

Plug #2 with 75 sxs Class B cement from 325' to surface to cover Mancos top (bottom of Mesaverde) and 7" casing shoe, circulate 1 bbl good cement out bradenhead to surface.

Plugging Summary:

Notified BLM on 8/19/97

8-19-98 Road rig and equipment to bottom of hill; road washed out. Wait for cat to repair road. SDFD.

8-20-98 Safety Meeting. Road rig and equipment to location, poor road conditions. RU rig and equipment. ND wellhead. PU on tubing; found 1 joint in well; LD joint. ND 5" wellhead and RU 8-5/8" x 4-1/2" wellhead. NU BOP and test. RU rig floor. Haul tubing from Navajo #23, 54 joints, for workstring. PU 4-1/2" casing scraper and tally in hole with 50 joints. Tag paraffin at 20'; continue to work casing scraper to 1560'. Circulate well clean with 20 bbls water. POH with scraper. PU 4-1/2" cement retainer and RIH; set at 1554'. Pressure test casing to 500#, held OK. Pressure test tubing to 1500#, held OK. Plug #1 with retainer at 1554', mix 47 sxs Class B cement; squeeze 24 sxs below retainer to fill Gallup perforations and leave 23 sxs above to cover top. POH and LD tubing. Shut in well. SDFD.

8-21-98 Safety Meeting. RU A-Plus wireline truck. Perforate 2 HSC squeeze holes at 325'. Establish circulation down casing and out bradenhead with 20 bbls water. Plug #2 with 75 sxs Class B cement from 325' to surface to cover Mancos top (bottom of Mesaverde) and 7" casing shoe, circulate 1 bbl good cement out bradenhead to surface. Shut in well and WOC. ND BOP and cut off wellhead. Mix 24 sxs Class B cement and install P&A marker. RD rig and equipment. J. Sanchez, BLM was on location.