UNITED STATES DEPARTMENT OF THE INTERIOR

UNITED STATES	5. LEASE 20 2 2 2 5 5 5
DEPARTMENT OF THE INTERIOR	14-20-603-585
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	Navajo Tribe - GNE
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME: B con
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	9m
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME HE DO N
1. oil gas	Navajo AA 🚊 Š
well well other	9. WELL NO. 11630
2. NAME OF OPERATOR	#5 20 316 29 15
James P. Woosley	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	No. Many Rocks Lower Gallup
P.O. Drawer 1480, Cortez, Colorado 81321 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
below.)	
AT SURFACE: 708' FNL & 1999' FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same	San Juan 3 8 9 Now Mexico
AT TOTAL DEPTH: Same	14. API NO. 프콜음의 리 오름등이
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	moi mar
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DE KOB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5350 GL 🔓 📅 💲 🐧 🏂 💆
TEST WATER SHUT-OFF \Box	6 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
FRACTURE TREAT	필 속등라 - 변 첫월속 ⁶
SHOOT OR ACIDIZE	VED THE THE SECOND SECO
PULL OR ALTER CASING []	(NOTE: Report results of multiple completion or zone
MULTIPLE COMPLETE TO SEP 2 3 19	change on Form 9-330.):
CHANGE ZONES	NAGEMENT - POTE P-330.)
ABANDON* BUREAU OF LAND MAN	NAGEMENT
(other) FARMINGTON RESOU	RCE AREA : ខ្លាក់ប្រាក់ គឺ គឺ ទីនួន 💥 🗀
including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner Plan to plug and abandon well as follows weat 1. Run 2-3/8" tubing to 1440' and fill hole 2. Place plug from 1440' back to 1390' with	ther permitting and rig availability: with gelled mud.
2. Place plug from 1440' back to 1390' with 5.0 cu. ft. of neat slurry rement. 3. Shoot 4-1/2" casing off above cement behind casing and pull. 100' Flagge ross cases.	
4. Run tubing and place plug from 100' back	to surface with 10.87 of the
of neat slurry cement.	
5. Clean location.	## 4
6. Place proper plug and abandon marker.	हिन्दु होते । अपने के के किया है । अपने
7. Reseed location with recommended seed.	11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	Attended to the second of the
	A CONTRACTOR OF THE STATE OF TH
Subsurface Safety Valve: Manu. and Type	Set con 4 to 2 Ft.
	200 A 8 A 8 A 8 A 8 A 8 A 8 A 8 A 8 A 8 A
18. I hereby certify that the foregoing is true and correct	Constant of the constant of th
SIGNED Office Manag	er DATE 54579-19-85738
(This space for Federal or State of	fice use)
CONDITIONS OF APPROVAL, IF ANY IS TITLE	DATE TAKEN TO THE TAKEN TH
	AS AMENUEL
(D) E W B - P	1 - 2 - 2 0 100 E
101 1985	852 26 1799
SEP 3 U 130 See Instructions on Reverse	
	Total Pall
NMOCC NMOCC	MILLENBACH
APPROVED BY CONDITIONS OF APPROVAL, IF ANY ED TITLE SEP 3 0 1985 OIL CON. DIV NMOCC DIST. 3	AREA MANAGER