STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT This form is not to be used for reporting packer leakage tests in Southeast New Mexico

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

perator Bi	URLINGTON RES	OURCES	OIL & GAS CO.		Lease	HUBBARD			Well No. 2	
ocation										
	Unit M	Sect 1	1 Twp.	032N	Rge.	012W	County	SAN JUAN	DROD MEDIUM	
W CII.	NAME OF RESERVOIR OR POOL					TYPE OF PROD. METHOD OF I			PROD. MEDIUM	
						(Oil or Gas)	(Flov	v or Art. Lift)	(Tbg. or Csg.)	
Upper Completion	MESAVERDE					Gas Flow		Flow	Casing	
Lower Completion	DAKOTA					Gas Flow		Flow	Tubing	
			PRE-F	LOW SHUT-IN	PRESS	URE DATA				
Upper	Hour, date shut-in Length of time shut-in					SI press. psig		Stabilized? (Yes or No)		
Completion	9/17/99		120 Hours		583					
Lower	3117700									
Completion	9/17/99		72 Hours		862					
	0,1			FLOW TE	ST NO.					
Commence	d at (hour,date)*		9/20/99			Zone producing (Upper or Lower) LOWER				
TIME	LAPSED TI	D TIME PRESSURE			PROD. ZONE		REMARKS			
(hour,date)	SINCE*	[Upper Completion	Completion Lower Comple		TEMP	REMARKS			
9/21/99	96 Hours	s	583	83 277			took	took shut in pressure, turned on DK.		
9/22/99	120 Hou	rs	584	288	The second secon		took	took pressures.		
					took pressures, turned		ned on MV.			
			E ST.	NE CO						
				ner		2 1 1099				
				is in Diag	<u>-</u>	TOWN/S				
Production r	ate during test			學出他	JW William	<u>a (5000</u> S				
Oil:	: BOPD based on		Bbls. in		Hours.		Grav.	· · · · · · · · · · · · · · · · · · ·	GOR	
						and the second				
Gas:			MCFPD; Tested thru	ı (Orifice or Me	ter):					
			MII	D-TEST SHUT-	IN PRE	SSURE DATA				
Upper Completic	per Hour, date shut-in		Length of time shut-in		SI press. psig				? (Yes or No)	
Lower	r Hour, date shut-in Length of time shut-in		ut-in	S	SI press. psig Stabilized			? (Yes or No)		

(Continue on reverse side)

Commenced at (hour, d	late)**		FLOW TEST NO				
TIME	LAPSED TIME SINCE **	PRESSURE		Zone producing (Upper or Lower):			
(hour, date)		Upper Completion	Lower Completion	PROD. ZONE TEMP.	REMARKS		
•							
							
Production rate dur	ing test						
Pil:	BO	PD based on	Bbls. in	Hours	GravGOR		
ras:		MCFPD:	Tested thru (Orifi	ce or Meter):	Gav		
emarks:			,				
hereby certify that	DEC 2.1	1000		best of my knowledge			
New Mexico Oil	Conservation Division	19_ on		perator Burlington R	esources		
CAIG	INAL SIGNED BY C	WILLE T. PETERN	В	y Aldrew Way	×		
nepun	OIL & GAS INSPE	CTOR, DIST. #3	Т	itle <u>Operations Associ</u>	ate		
le			D	ate Friday, October 08	3, 1999		

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- l. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the jubing have been disturbed. Tests shall also be taken at any time that communication is sus; ected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an ii-tial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipe one connection the flow period shall be three hours.
- 5- dollowing completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above
- low Test No. 2 shall be conducted even though no leak was indicated during Flow Test
 Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was π eviously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweig it pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and a hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be aken as desired, or may be requested on wells which have previously shown questionable lest data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be contiruously started and recorded with recording pressure gauges the accuracy of which mus be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 drys after completion of the test. Tests shall be filed with the Aztec District Office of the Ne v Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Levised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing ter iperatures (gas zones only) and gravity and GOR (oil zones only).