

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S. G.S.	
OPERATOR	1

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. <b>E-3151-1</b>

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> WELL GAS <input checked="" type="checkbox"/> WELL OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator <b>PUBCO PETROLEUM CORP.</b>	8. Farm or Lease Name <b>State Com. AJ</b>
3. Address of Operator <b>P.O. Box 869, Albuquerque, New Mexico</b>	9. Well No. <b>34</b>
4. Location of Well UNIT LETTER <b>D</b> , <b>790</b> FEET FROM THE <b>North</b> LINE AND <b>790</b> FEET FROM THE <b>West</b> LINE, SECTION <b>36</b> TOWNSHIP <b>32 North</b> RANGE <b>12 West</b> NMPM.	10. Field and Pool, or Wildcat <b>Basin Dakota</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>6404 Gr. 6416 KB</b>	12. County <b>San Juan</b>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-26-67: Ran 236 joints 4½", 10.5#, J-55, ST&C casing; landed at 7673' KB.  
Cemented in single stage with 160 sax Class "C" cement, 12% gel, 1% CFR-2,  
6#/sk. salt and 12½#/sk. gilsonite, followed by 80 sax Class "C" cement,  
16% gel, 1% CFR-2, 6#/sk salt, 12½#/sk gilsonite, followed by 120 sax  
Class "C" , 50/50 Pommix S, 7#/sk. salt and ½% CFR-2.  
Bumped plug with 1500 psi.  
Plug down at 1:45 A.M. 2-26-67. Calculated cement top at 4000'.

Tested casing with 1500 psi. Test OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Donald P. Walker TITLE Petroleum Engineer DATE March 2, 1967  
APPROVED BY Everett Clavel TITLE Superintendent DATE 3-6-67  
CONDITIONS OF APPROVAL, IF ANY: