

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

14-20-603-583

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Navajo B

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Mesa Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 15, T32N, R18W

12. COUNTY OR PARISH
San Juan

13. STATE
N. M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

AAA Fishing Tool Co., Inc.

3. ADDRESS OF OPERATOR

Box 234, Farmington, N. M. 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1150' fnl 1480' fe1

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
5318' Gr.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3/20/70 Spudded 8 3/4" hole 3/19/70 set 12' of 7" csg. @ 12' GI.-cemented with 5 sx. to surface. Drilled 5 5/8" hole with air to 400' - shut down.

3/21/70 1000'

Air

3/22/70 T.D. 1292'. Had show of oil at 1195' - cuttings became oil saturated but hole cased to T.D.

3/23/70 Ran 39 jts. 4 1/2" O.D., 9.5#, 8R, ST&C csg. T.E. 1274.08' set @ 1275' Gr. level. Cemented with 35 sx. Class "A" with 9/10 % Haled 9-followed plug with 250 gal. Acidic Acid; displaced plug with oil. P.O.B. 1:30 p.m., 3/22/70 - no cement to surface.

RECEIVED

JUL 23 1970

U. S. GEOLOGICAL SURVEY
FARMINGTON

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

Engineer

DATE

7/22/70

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: