

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Sundry Notices and Reports on Wells

1. Type of Well
Oil
2. Name of Operator
Petroleum
Texas Pacific Oil & Gas Co., C/O Joseph E. Seagram & Sons, Inc.
3. Address & Phone No. of Operator
800 3rd Ave., New York City, NY 10022-7699
4. Location of Well, Footage, Sec., T, R, M
360' FSL and 2310' FEL Sec. 27, T-32-N, R-17-W, NMPM
0
5. Lease Number
14-20-603-5012
6. If Indian, All. or
Tribe Name
Navajo
7. Unit Agreement Name
N/A
8. Well Name & Number
Navajo #14
9. API Well No.
30-045-2190300
10. Field and Pool
Many Rocks
11. County & State
San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

Texas Pacific Oil & Gas Co., plugged and abandoned this well on March 31, 1997,
per the attached Plug & Abandonment report.

RECEIVED
APR - 8 1997

14. I hereby certify that the foregoing is true and correct.

Signed

William F. Clark

Title

Contractor

Date 4/2/97

William F. Clark, President A-Plus Well Service

OIL CON. DIV.
DIST. 3

(This space for Federal or State Office use)

APPROVED BY

Carol B. Baker

Title

Deputy Director

Date

APR 1 1997

CONDITION OF APPROVAL, if any:

NMOC

A - PLUS WELL SERVICE, INC.

P.O. BOX 1979
FARMINGTON, NM 87499
505-325-2627 • FAX: 505-325-1211

Texas Pacific Oil & Gas Co.,
c/o Joseph E. Seagram & Sons

Navajo #14

360' FSL and 2310' FEL, Sec. 27, T-32-N, R-17-W,
San Juan County, NM
BIA 14-20-603-5012

APR 2 1997

Plug & Abandonment Report

Cementing Summary:

Plug #1 with 48 sxs Class B cement from 1696' to 1075' to fill Gallup perforations and cover top.

Plug #2 with 88 sxs Class B cement pumped down casing from 325' to surface, to cover Mesaverde top; circulate good cement to surface out 7" annulus.

Plugging Summary:

Notified BLM on March 26, 1997

3-27-97 Company Safety Meeting. Road rig to location. RU rig and equipment. Open up well, no pressures. Install wellhead. NU BOP. RU rig floor and tubing equipment. PU perf plugging sub; too windy to RIH with tubing. Shut in well. SDFD.

3-31-97 Safety Meeting. PU and RIH with 2-3/8" tubing; tag bottom at 1702'. Establish circulation with 5 bbls water. Plug #1 with 48 sxs Class B cement from 1696' to 1075' to fill Gallup perforations and cover top. POH to 331'. Shut in well and WOC. Open up well and RIH; tag cement at 1196'. Load casing with 3 bbls water and pressure test to 500# for 10 min, held OK. POH and LD tubing. RU A-Plus wireline truck. Perforate 2 squeeze holes at 325'. Establish circulation down 4-1/2" casing and out 7" bradenhead annulus with 20 bbls water. Plug #2 with 88 sxs Class B cement pumped down casing from 325' to surface, to cover Mesaverde top; circulate good cement to surface out 7" annulus. Shut in well and WOC. Open up well; bradenhead went on a vacuum. SDFD.

4-1-97 Open up well, no pressure. ND BOP. Remove wellhead and flange. Cut wellhead off; found cement down 15' in 4-1/2" casing and 25' in 7" annulus. Mix 31 sxs Class B cement, fill casing and annulus; then install P&A marker. RD rig and equipment; move off location.
J. Sanchez, BLM representative was on location.