

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well
2. NAME OF OPERATOR
ENP6
3. ADDRESS OF OPERATOR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 800'N, 1180'W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☒
☐
☐
☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/30/77: T.D. 3306'. Ran 80 joints 7", 20#, K-55 intermediate casing, 3295' set at 3306'. Cemented with 515 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 1475'.

9/3/77: T.D. 5642'. Ran 78 joints 4 1/2", 10.5#, K-55 casing liner, 2506' set 3136-5642'. Float collar set at 5625'. Cemented with 435 cu. ft. cement. WOC 18 hours.

1/7/78: PBD 5625'. Tested casing to 3500#, OK. Perfed P.C. 2880-2900, 2908-14, 2924-44' w/16 SPZ. Fraced with 54,000# 20/40 sand and 54,041 gallons water. Dropped 2 sets of 16 balls each. Flushed with 4914 gallons water. Perfed C.H. 4461-66', 4503-10, 4546-58, 4641-62, 4662-82, 4725-39' w/16 SPZ. Fraced with 88,000# 20/40 sand and 88,023 gallons water. Dropped 5 sets of 16 balls each. Flushed

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft. (OVER)

18. I hereby certify that the foregoing is true and correct

SIGNED N. D. Busco TITLE Drilling Clerk DATE 1/16/78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

5. LEASE SF 078051	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME Neil	
9. WELL NO. 7A (PM)	
10. FIELD OR WILDCAT NAME Blanco P.C. Blanco M.V.	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 33, T-32-N, R-11-W NMPM	
12. COUNTY OR PARISH San Juan	13. STATE New Mexico
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 6192' GL	

RECEIVED

JAN 18 1978

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-149

with 6216 gal. water. Perfed Men. 4833-43, 4853-76, 4906-18, 4951-59, 4969-76, 5013-29, 5039-55, 5065-73, w/16 SPZ. Fraced with 81, 727# 20/40 sand and 81, 727 gallons water. Dropped 6 sets of 16 balls each. Flushed with 12, 939 gal. water. Perfed Upper P.L. 5162-85, 5195-99, 5225-37, 5247-59, 5273-83, 5293-5311' w/16 SPZ. Fraced w/90,000# 20/40 sand and 90,055 gallons water. Dropped 5 sets of 16 balls each. Flushed w/6678 gal. water. Perfed Lower P.L. 5379-85, 5417-25, 5435-47, 5479-91, 5504-11, 5521-27, 5539-48, 5559-71, 5590-5601' w/16 SPZ. Fraced w/33,000# 20/40 sand and 24,000 gallons water. Dropped 3 sets of 16 balls each. Perfs bailed off when third set of balls hit, no flush. Re-fraced w/28,000# 20/40 sand and 33,018 gallons water. Dropped 4 sets of 16 balls each. Flushed w/4830 gal. water.