SUBMIT IN TRIPLICATE*

(Other instructions on reverse side)

Form approved. Budget Bureau No. 42-R1425.

UNITED STATES

(MRR Law)	UNIT	ED STATES	NTER	reverse sid	le) í	30 - 045 - 3	2611	
DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY						57 FARE DESIGNATION 2ND SERIAL NO. Ind-2772		
A DDL IC A TION				N. OR PLUG BA	ACK	6. IF INDIAN, ALLOTTEE O	R TRIBE NAME	
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK DRILL DEEPEN PLUG BACK						Ute Mountain 7Barker Creek Dome Gas		
b. TYPE OF WELL OIL GAS			818	IGLE MULTIPL		Storage Pro		
WELL WE		Gas Stor	agen	NE LX ZONE		Storage Pro		
El Paso Na	tural Gas Co	mpany				WI #21		
	. Farmington	. NM 874	101_			10. FIELD AND POOL, OR	WILDCAT	
PO BOX 990 4. LOCATION OF WELL (Re	port location clearly and 2268'N, 75	Barker Cree! 11. SEC., T., R., M., OR BL. AND SURVEY OR AREA	K.					
At proposed prod. zone		•				Sec.21,T-32	-N,R-14-W	
14. DISTANCE IN MILES A	ND DIRECTION FROM NEAR	REST TOWN OR POS	T OFFICE	•		12. COUNTY OR PARISH	13. STATE	
					1 17 NO (San Juan OF ACRES ASSIGNED	NM	
15. DISTANCE FROM PROPOSED® LOCATION TO NEAREST			acres-14,728 N/A			OF ACRES ASSIGNED HIS WELL		
PROPERTY OR LEASE LI (Also to nearest drig 18. DISTANCE FROM PROPE	unit line, if any)			OPOSED DEPTH		RY OR CABLE TOOLS	·	
TO NEAREST WELL, DE OR APPLIED FOR, ON THE	HLLING, COMPLETED,			2375'	Rota			
21. ELEVATIONS (Show whe	ther DF, RT, GR, etc.)					July 15, 19		
23.		PROPOSED CASI	NG AND	CEMENTING PROGRA	AM			
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER F	тоот	SETTING DEPTH		QUANTITY OF CEMENT		
12 1/4"	9 5/8"	32.3# H		430'		cu.ft.to circ		
8_3/4"	7"	20.0# K				cu.ft.to fill 400' above .ng shoe		
					[Cubi.			
Dakota for 7" casing	mation. The seat to the	e well wi total de	pth o	e completed of 2375'. gas storage	in t	g depth into hole from the		
customers	east of Cal	ifornia.		rage gas wil		ALLE IN STATE OF THE STATE OF T		
in above space describe zone. If proposal is to preventer program, if an	drill or deepen direction	proposal is to de nally, give pertine	epen or nt data	plug back, give data on pon subsurface locations a	present pro ind measur	ed and true vertical enth	new productive	
81GNED SIGNA	Bushe	[d	TTLE	Drilling	Cler	k Jur	e 10, 197	
(This space for Fed	eral or State office use)							
PERMIT NO.				APPROVAL DATE				
APPROVED BY		1	eitik			DATE		

*See Instructions On Reverse Side

Form C-102 Supersedes C-128 Effective 1-1-65

All distances must be from the outer boundaries of the Section Well No. Lease UTE MTN. TRIBAL I-22-IND-2772 Operator EL PASO NATURAL GAS COMPANY WI-21 BARKER CREEK DOME GAS STORAGE PROJECT County Township Section Unit Letter 14-W SAN JUAN 32-N 21 Actual Footage Location of Well: 2268 NORTH feet from the feet from the Dedicated Acreage: Producing Formation Ground Level Elev. N/A DAKOTA Acres 6178 1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below. 2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty). 3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling. etc? If answer is "yes," type of consolidation. Yes If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.). No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission. CERTIFICATION I hereby certify that the information contained herein is true and complete to the of my knowledge and belief. GINAL SIGNED BY Sr.Drilling Engineer El Paso Natural Gas June 10, 1977 15 SECTION 21 I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the some is true and correct to the best of my knowledge and belief. Date Surveyed APRIL 21, 1977 Registered Professional Engineer and/or Land Surveyor Certificate No.

1000



R. O. BOX 990 FARMINGTON, NEW MEXICO 87401 PHONE: 505-325-2841

Multi-Point Surface Use Plan Barker Creek Dome Gas Storage Project WI #21

- Please refer to Map No. 1 which shows the existing roads. New roads which will be required have been marked on this map.
 All existing and new roads will be properly maintained during the duration of this project.
- 2. Planned Access Roads Please refer to Map No. 1. The grade of the access roads will be consistent with that of the local terrain. The road surface will not exceed twenty feet (20') in width. Upon completion of the project, the access road will be adequately drained to control soil erosion. Drainage facilities may include ditches, water bars, culverts or any other measure deemed necessary by trained Company personnel to insure proper drainage. Gates and/or cattleguards will be installed if necessary.
- 3. Location of Existing Wells Please refer to Maps No. 1 and No. 2.
- 4. Location of Tank Batteries, Production Facilities, and Production
 Gathering and Service Lines Please refer to Maps No. 1 and No. 2.

 Map No. 2 shows the existing gas gathering
 lines. Map No. 1 shows the existing roads and
 new proposed access roads. All known production
 facilities are shown on these two maps.
- 5. Location and Type of Water Supply Water for the proposed project will be obtained from El Paso Natural Gas Company's San Juan River Plant.
- 6. Source of Construction Materials No additional materials will be required to build either the access road or the proposed location.

- 7. Methods of Handling Waste Materials - All garbage and trash materials will be put into a burn pit shown on the attached Location Plat No. 1. clean-up operations are begun on the proposed project, the burn pit with its refuse will be buried to a depth of at least three feet (3'). A latrine, the location of which is also shown on Plat No. 1 will be provided for human waste. If large amounts of liquids are left in the reserve pit after completion of the project, the pit will be fenced until the liquids have had adequate time to dry. The location clean-up will not take place until such time as the reserve pit can be properly covered over to prevent run-off from carrying any of these materials into the watershed. No earthen pit will be located on natural drainages; all earthen pits will be so constructed as to prevent leakage from occurring.
- 8. Ancillary Facilities No camps or airstrips will be associated with this project.
- 9. Wellsite Layout Please refer to the attached Plat No. 1.
- 10. Plans for Restoration of the Surface After completion of the proposed project, the location will be cleaned and leveled. The location will be left in such a condition that will enable reseeding operations to be carried out. Seed Mixture #2 will be used. The reseeding operation will be performed during the time period set forth by the regulatory body. The location production equipment will be painted Forest Green.
- 11. Other Information -The immediate terrain is shale ridges with cedar, pinon trees. Deer and cattle inhabit the area.

- 12. Operator's Representative W. D. Dawson, Post Office Box 990, Farmington, New Mexico 87401
- 13. Certification -

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drillsite and access route; that I am familiar with the conditions which presently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and, that the work associated with the operations proposed herein will be performed by El Paso Natural Gas Company and its contractors and sub-contractors in conformity with this plan and the terms and conditions under which it is approved.

June 10, 1977

L. A. Aimes

Sr. Drilling Engineer

LAA:pb

Operations Plan Barker Creek Dome Gas Storage Project WI #21

I. Location: 2268'N, 75'W, Section 21, T-32-N, R-14-W, San Juan County, NM

II. Geology:

- A. Formation Tops: Mesa Verde --- Greenhorn 2145'
 Menefee surface Graneros 2205'
 Point Lookout 30' Dakota 2275'
 Mancos 390' Total Depth 2375'
- B. Logging Program: GR-I, FDC, SNP at 7" casing seat GR-I, FDC, SNP, GR-N at TD.
- C. Coring Program: 420' of core will be cut beginning at 1945'
- D. Natural Gauges: gauge well every connection past 2235' and at TD. Record all gauges in daily drilling report and on morning report.

III. Drilling:

A. Mud Program: mud on surface hole. Air from surface casing depth to Total Depth.

IV. Materials:

A.	Casing Program:	Hole Size	<u>Depth</u>	Csg.Size	Wt.&Grade
		12 1/4" 8 3/4"	430' 2277'	9 5/8" 7"	32.3# H-40 20.0# K-55
		6 1/4"	2277-2375'	,	20.0# K-33

B. Float Equipment: 9 5/8" surface casing - notched collar for guide shoe.


7" intermediate casing - cement guide shoe and self-fill insert float valve. Run float two joints above shoe.

- C. Tubing: 2360' of 2 3/8", 4.7#, J-55 8rd EUE tubing.
- D. Wellhead Equipment: 10" 2000 psi x 9 5/8" Type R Brewster casing head. 10" 2000 psi x 6" 2000 psi Type 2-082-77 Brewster xmas tree assembly.

V. Cementing:


9 5/8" surface casing - use 228 sks. of Class "B" cement with 3% calcium chloride (269 cu.ft. of slurry, 100% excess to circulate to surface). WOC 12 hours. Test casing to 600#/30 minutes.

7" intermediate casing - use 76 sks. of Class "B" cement with 2% calcium chloride (90 cu.ft. of slurry, 50% excess to fill 400' above the casing shoe). Run temperature survey at 8 hours. WOC 12 hours. Test casing to 1200#/30 minutes.



Scries 900 Double Gate BOP, rated at 3000 psi Working Pressure
When airdrilling operations begin a Shaffer type 50 or equivalent rotating head is installed on top of the flow nipple and the flow line is converted into a blowie line.

11'116 Con To Day 0' 230 ٥,



El Paso Natural Gas Company

Well Name: WI #21

Location: 2268'N, 75'W, Section 11 T-32-N,R-14-W, San Juan County, NM

Map #1

Proposed pipeline & road

