UNITED STATES

SF	 07	80)5	1	7 4 5	

5. LEASE

DEPARTMENT OF THE INTERIOR	SF 0/8051
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME
reservoir. Use Form 9-331-C for Sucil proposals.)	8. FARM OR LEASE NAME 8 1945 Neil 8384 6 853
1. oil gas k other	9. WELL NO. \$ 7.5
2. NAME OF OPERATOR	6A (PM)
EL PASO NATURAL GAS CO.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Blanco MV-Blanco PC
BOX 289, FARMINGTON, NEW MEXICO	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 33, T-32-N, R-11-W
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	ANLA Sec. 33, 1-32-N, K-11-W
below.) AT SURFACE: 790'S, 1540'E	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	San Juan New Mexico
AT TOTAL DEPTH:	14. API NO. 글롤루팅 및 원통하
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	\$ 0.00 ft 100 ft
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6127 GR 6876 8 646
TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9–330.)
MULTIPLE COMPLETE	
CHANGE ZONES	ု မိုးရှိနှင့် မေးရှိသည်။ မိုးရှိနှင့် မေးရှိသည်။
ABANDON* U (other)	
	<u> </u>
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is different measured and true vertical depths for all markers and zones pertined	re all pertinent details, and give pertinent dates, lirectionally drilled, give subsurface locations and nt to this work.)*
	· · · · · · · · · · · · · · · · · · ·
1/16/79: Pulled tubing and pressure teste	ed casing to 3500#, OK.
1/17/79: PBTD 5523'. Perfed PC formation	
w/16 SPZ. Fraced w/58,000# 10/20 sand and	
of 16 balls each. Flushed w/5070 gal. wat	ter. #PANA PANA PANA
1/19/79: Ran Baker Model D Packer set at 4.7#, J-55 Mesa Verde tubing 5382' set at Ran 90 joints 1 1/4, 2.4#, V-55 tubing 29% at 2903'.	5392'. Seating Nipple at 5360'.
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED A. BHORD TITLE Drilling Cle	rk date <u>2/2/79</u>
(This space for Federal or State of	fice use) 1 0 1 1 1 1 1 1 1 1
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	Sun of the
	A Section of the property of t

AMOCCOIL DIST. 3