STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator BI	JRLINGTON RESOURCE	S OIL & GAS CO.	I	Lease	DALSANT			Well No. <u>1A</u>
Location								
of Well:	Unit Sect	24 Twp.	032N I	Rge.	012W	County	SAN JUAN	
	NAME OF	RESERVOIR OR POO	L	T	PE OF PROD.	METH	OD OF PROD.	PROD. MEDIUM
					(Oil or Gas)	(Flo	w or Art. Lift)	(Tbg. or Csg.)
Upper Completion	PICTURED CLIFFS				Gas	Gas Flow		Tubing
Lower Completion	MESAVERDE				Gas			Tubing
			LOW SHUT-IN I	PRESS	SURE DATA			
Upper	Hour, date shut-in Length of time shut-in			SI press. psig Stabiliz			Stabilized? (Y	es or No)
Completion	9/17/99 14		Hours		478			
Lower Completion	9/17/99	192 Ho	urs		66			
		-	FLOW TEST	NO.	1			
Commenced at (hour,date)* 9/23/99				Zone producing (Upper or Lower)			Lower) UF	PER
TIME	LAPSED TIME	PRES	SSURE		PROD. ZONE			
(hour,date)	SINCE*	Upper Completion	Lower Complet	tion	ТЕМР	TEMP RE		MARKS
9/24/99	168 Hours	362	66			Lower zone on comp.		
9/25/99	192 Hours	347	347 66				the second	
								661 2 7 1939 m
							OLL	, (36) 13. una 3. - 12:33. 3
Production rate	during test						Nagara da ana	
Oil:	BOPD based on Bbls. in		n	Hours.		Grav.	7 GOR	
Gas:		MCFPD; Tested thru ((Orifice or Meter):	·				
		MID-	TEST SHUT-IN I	PRESS	SURE DATA			
Upper Completion	Hour, date shut-in	Length of time shut-in		SI press. psig			Stabilized? (Yes or No)	
Lower Completion	Hour, date shut-in	Length of time shut-in		SI press. psig			Stabilized? (\)	(es or No)

(Continue on reverse side)

FLOW TEST NO. 2 Commenced at (hour, date)** Zone producing (Upper or Lower): PRESSURE TIME LAPSED TIME PROD. ZONE REMARKS (hour, date) SINCE " **Upper Completion** Lower Completion Production rate during test Oil: ______BOPD based on _____Bbls. in ____Hours ____Grav. ____GOR _____ Gas: MCFPD: Tested thru (Orifice or Meter): Remarks: I hereby certify that the information herein contained is true and complete to the best of my knowledge OCT 27 1999 19 Operator New Mexico Oil Conservation Division ORIGINAL SIGNED BY CHAPLLE T. PERFEM By By _____ BRYITY OIL & GAS INSPECTOR, DIST, 43 Title Operations Associate

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Title ____

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Tes No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

Date Friday, October 08, 1999

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas thal completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztee District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).