UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

	Budget Bureau No. 42-R1424
	5. LEASE 2503 C 884
	SF 078147
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
_	<u> </u>
	7. UNIT AGREEMENT NAME:
t	<u></u>
	8. FARM OR LEASE NAME
	Moore
	9. WELL NO.
	5A (PM)
	10. FIELD OR WILDCAT NAME
_	Blanco P.C. Ext & Blanco M.V
	11. SEC., T., R., M., OR BLK. AND SURVEY OR
,	AREA Sec. 24, T-32-N, R-12-W
	N.M.P.M.
	12. COUNTY OR PARISH 13. STATE
	San Juan - New Mexico
_	14. API NO. 원들장 후 원급합
	그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그

SUNDRY NOTICES AND REPORTS ON	WELLS 7. UNIT AGREEMENT NAME:
(Do not use this form for proposals to drill or to deepen or plug bareservoir. Use Form 9–331–C for such proposals.)	ack to a different
1 oil goe	8. FARM OR LEASE NAME SANGE MOORE
well gas	9. WELL NO.
2. NAME OF OPERATOR	5A (PM)
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Blanco P.C. Ext & Blanco M.V
P.O. Box 289, Farmington, New Mexic 4. LOCATION OF WELL (REPORT LOCATION CLEARLY.	
below.)	N.M.P.M.
AT SURFACE: 2000'N, 800'W	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan - New Mexico
	14. API NO.
 CHECK APPROPRIATE BOX TO INDICATE NATURE REPORT, OR OTHER DATA 	
ne. on on one one	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT RE	EPORT OF:
TEST WATER SHUT-OFF	មីពីស្តីដ ភេទស្ថិក ។ សុទ្ធិ
FRACTURE TREAT	The state of the s
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330.)
MULTIPLE COMPLETE CHANGE ZONES	
ABANDON*	ं क्षेत्र हैं। अं क्षेत्र के किया है
(other)	That is have been a bottom to be the control of the
17 DESCRIBE PROPOSED OR COMPLETED OPERATION	IS (Clearly state all pertinent details, and give pertinent dates
including estimated date of starting any proposed w	ork. If well is directionally drilled, give subsurface locations and
including estimated date of starting any proposed we measured and true vertical depths for all markers and	ork. If well is directionally drilled, give subsurface locations and d zones pertinent to this work.)* 출동 등을 걸 걸 구 된
including estimated date of starting any proposed we measured and true vertical depths for all markers and	ork. If well is directionally drilled, give subsurface locations and d zones pertinent to this work.)* ਜ਼ਿੰਨ ਤੋਂ ਤੋਂ ਜ਼ਿੰਦ ਹੈ ਹੈ ਜ਼ਿੰਨ ਤੋਂ ਜ਼ਿੰਨ
measured and true vertical depths for all markers and 4-20-79: Spudded well. Drilled su	ork. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* ###################################
4-20-79: Spudded well. Drilled su surface casing, 206' set	ork. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* urface hole. Ran 5 jts, 9 5/8", 36#, K-55 at 220'. Cemented w/224 cu. ft. cement.
4-20-79: Spudded well. Drilled su surface casing, 206' set	ork. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* ###################################
4-20-79: Spudded well. Drilled su surface casing, 206' set	ork. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* urface hole. Ran 5 jts, 9 5/8", 36#, K-55 at 220'. Cemented w/224 cu. ft. cement.
4-20-79: Spudded well. Drilled su surface casing, 206' set	ork. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* urface hole. Ran 5 jts, 9 5/8", 36#, K-55 at 220'. Cemented w/224 cu. ft. cement.
4-20-79: Spudded well. Drilled su surface casing, 206' set	ork. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* arface hole. Ran 5 jts: 905/8"; 36#, K-55 at 220'. Cemented w/224 cu. ft. cement. OC 12 hours; held 600#/30 minutes: and gives and gives a subsurface locations and gives a subsurface location and
4-20-79: Spudded well. Drilled su surface casing, 206' set	ork. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* arface hole. Ran 5 jts: 9.5/8", 36#, K-55 at 220'. Cemented w/224 cu. ft. cement. OC 12 hours; held 600#/30 minutes. And limentary and li
4-20-79: Spudded well. Drilled su surface casing, 206' set	ork. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* arface hole. Ran 5 jts: 9.5/8", 36#, K-55 at 220'. Cemented w/224 cu. ft. cement. OC 12 hours; held 600#/30 minutes. And limentary and li
4-20-79: Spudded well. Drilled su surface casing, 206' set	ork. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* arface hole. Ran 5 jts: 9.5/8", 36#, K-55 at 220'. Cemented w/224 cu. ft. cement. OC 12 hours; held 600#/30 minutes. And limentary and li
4-20-79: Spudded well. Drilled su surface casing, 206' set	ork. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* arface hole. Ran 5 jts: 905/8"; 36#, K-55 at 220'. Cemented w/224 cu. ft. cement. OC 12 hours; held 600#/30 minutes: and gives and gives a subsurface locations and gives a subsurface location and
including estimated date of starting any proposed we measured and true vertical depths for all markers and 4-20-79: Spudded well. Drilled su surface casing, 206' set Circulated to surface. We have a surface with the surface were surface.	ork. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* arface hole. Ran 5 jts. 95/8"; 36#; K-55 at 220'. Cemented w/224 cu. ft. cement. OC 12 hours; held 600#/30 minutes and fill was work and a work at 5 to 30
including estimated date of starting any proposed we measured and true vertical depths for all markers and 4-20-79: Spudded well. Drilled su surface casing, 206' set Circulated to surface. We have a surface with the surface were surface.	ork. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* arface hole. Ran 5 jts. 95/8"; 36#, K-55 at 220'. Cemented w/224 cu. ft. cement. OC 12 hours; held 600#/30 minutes and substitution loose by the substitution of grands are the
including estimated date of starting any proposed we measured and true vertical depths for all markers and 4-20-79: Spudded well. Drilled su surface casing, 206' set Circulated to surface. We were surface with the surface surface with the surface surface with the surface surface.	ork. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* arface hole. Ran 5 jts. 95/8"; 36#; K-55 at 220'. Cemented w/224 cu. ft. cement. OC 12 hours; held 600#/30 minutes and fill was work and a work at 5 to 30
including estimated date of starting any proposed we measured and true vertical depths for all markers and 4-20-79: Spudded well. Drilled su surface casing, 206' set Circulated to surface. We support the surface well and the surface well are surface. We support that the foregoing is true and correct to the surface well and the surface well as the support of the surface well as the support of the surface well as the support of the support of the surface well as the support of the su	ork. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* arface hole. Ran 5 jts. 95/8"; 36#, K-55 at 220'. Cemented w/224 cu. ft. cement. OC 12 hours; held 600#/30 minutes and substitution loose by the substitution of grands are the
Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED I measured and true vertical depths for all markers and warring and true vertical depths for all markers and true vertical depths for all markers and 4-20-79: Spudded well. Drilled su surface casing, 206' set Circulated to surface. Well surface was surface. Well surface with the foregoing is true and correct signed.	ork. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* arface hole. Ran 5 jts. 9 5/8", 36#, K-55 at 220'. Cemented w/224 cu. ft. cement. OC 12 hours; held 600#/30 minutes at a billional rate of the partial part and the provides of minutes at a billional rate of the partial of beinglass of the partial of bootlants of partial of partial of partial of partial of the partial of t
Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED I measured and true vertical depths for all markers and warring and true vertical depths for all markers and true vertical depths for all markers and 4-20-79: Spudded well. Drilled su surface casing, 206' set Circulated to surface. Well surface was surface. Well surface with the foregoing is true and correct signed.	ork. If well is directionally drilled, give subsurface locations and decores pertinent to this work.)* irface hole. Ran 5 jts. 95/8", 36#, K-55 at 220'. Cemented w/224 cu. ft. cement. OC 12 hours; held 600#/30 minutes at build always at the control of subsurface on

*See Instructions on Reverse Side