

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2000'N, 800'W

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☒
☐
☐
☐
☐
☐
☐
☐

5. LEASE
SF 078147

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Moore (PM)

9. WELL NO.
5A

10. FIELD OR WILDCAT NAME

Blanco PC Ext. & Blanco MV

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 24, T-32-N, R-12-W
N.M.P.M.

12. COUNTY OR PARISH

San Juan

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6468' G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-1-79: PBTB 5722'. Tested casing to 3500#, OK. Perfed Lower P.L. 5465,5471,5482, 5500,5517,5534,5544,5558,5580,5596,5608,5648,5661,5692' W/1 SPZ. Fraced with 39,000# 20/40 sand, 91,884 gal. water. Flushed w/6,888 gal. water.

8-2-79: Perfed MW Mass. PL&Men. 5105,5112,5138,5163,5187,5196,5307,5313,5319,5324,5346, 5353,5360,5374,5380,5386,5405,5411,5417,5430' W/1 SPZ. Fraced w/63,000# 20/40 sand, 126,000 gal. water. Flushed w/6,846 gal. water. Perfed P.C. 2906-2912 2924-2940,2940-2956,2972-2994,3026-3050,3054-3074' W/16 SPZ Fraced w/86,786# 10/20 sand, 96,786 gal. water. Dropped 4 sets of 16 balls each. Flushed w/ 5208 gal. water.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Drilling Clerk DATE August 3, 1979

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

