

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

AMOCO PRODUCTION COMPANY

3. ADDRESS OF OPERATOR

501 Airport Drive Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1840' FSL x 1180' FWL, Section 13,

AT SURFACE: T32N, R14W

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other)

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☒

5. LEASE MOO-C-1420-1729

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Ute Mountain Tribe

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Ute Mountain Tribal "O"

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Ute Dome Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA NW/4 SW/4, Section 13,

T32N, R14W

12. COUNTY OR PARISH 13. STATE

San Juan

NM

14. API NO.

30-045-23237

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6777' GL, 6787' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

As a result of the above well being unable to produce commercial quantities of gas, it was plugged and abandoned on 7/7/79 as follows:

- 1) Set cement retainer at 3031'. Squeezed through cement retainer with 135 sx Class "B" Neat cement. Locked up. Spotted 25 sx cement above retainer.
- 2) Spotted 10 sx Class "B" Neat cement at 2450'.
- 3) Spotted 5 sx Class "B" Neat cement at surface.
- 4) Cut off wellhead and erected P & A marker.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

Original Signed By

SIGNED E. E. SVOBODA

TITLE Dist. Adm. Supvr

DATE 7/10/79

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: