

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different formation. Use Form 9-331-C for such proposals.)

Oil ☐ gas ☒
well ☐ well ☒ other ☐

1. NAME OF OPERATOR

AMOCO PRODUCTION COMPANY

3. ADDRESS OF OPERATOR

501 Airport Drive Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

1840' FSL x 1180' FWL, Section 13,

AT SURFACE: T32N, R14W

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

5. LEASE

MOO-C-1420-1729

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Ute Mountain Tribe

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Ute Mountain Tribal "O"

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Ute Dome Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR

AREA NW/4 SW/4, Section 13,

T32N, R14W

12. COUNTY OR PARISH 13. STATE

San Juan

NM

14. API NO.

30-045-23237

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6777' GL, 6787' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

As a result of the above well being unable to produce commercial quantities of gas, it was plugged and abandoned on 7/7/79 as follows:

- 1) Set cement retainer at 3031'. Squeezed through cement retainer with 135 sx Class "B" Neat cement. Locked up. Spotted 25 sx cement above retainer.
- 2) Spotted 10 sx Class "B" Neat cement at 2450'.
- 3) Spotted 5 sx Class "B" Neat cement at surface.
- 4) Cut off wellhead and erected P & A marker.

RECEIVED

MAY 03 1984

OIL CON. DIV.

DIST. 3

Set @ _____ Ft.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Dist. Adm. Supvr DATE 7/10/79

(This space for Federal or State office use)

APPROVED BY David J. Miller TITLE Area Manager DATE MAY 1 1984

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

COPY TO ALBQ.

AMOCO