

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	4

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Southland Royalty Company	8. Farm or Lease Name Vasaly Federal
3. Address of Operator P. O. Drawer 570, Farmington, NM 87401	9. Well No. #2
4. Location of Well UNIT LETTER <u>I</u> , <u>1615</u> FEET FROM THE <u>South</u> LINE AND <u>900</u> FEET FROM THE <u>East</u> LINE, SECTION <u>31</u> TOWNSHIP <u>32N</u> RANGE <u>11W</u> NMPM.	10. Field and Pool, or Wildcat Blanco Pictured Cliffs
15. Elevation (Show whether DF, RT, GR, etc.) 6460' GR	12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <u>Spud and Casing Report</u> <input checked="" type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

10-8-79 Spudded 12 1/4" surface hole at 4:15 PM, 10-8-79 and drilled to 135'. Set 3 joints of 8 5/8", 24#, K-55 casing at 135'. Cemented with 195 sacks of Class "B" with 1/4# gel flake per sack and 3% CaCl₂. Cement circulated to surface. Plug down at 7:15 PM, 10-8-79.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE District Engineer DATE 10-9-79

Original Signed by A. R. Fordrich

SUPERVISOR DISTRICT # 3

DATE OCT 9 1979

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: