

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0101125A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

RINCON OPERATING CO.

3. ADDRESS OF OPERATOR

1860 Lincoln Street, #808, Denver, CO 80295

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface 1739' FWL & 2247' FSL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Ute Dome Federal

9. WELL NO.

#1

10. FIELD AND POOL, OR WILDCAT

Ute Dome Paradox

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 19, T32N, R13W

12. COUNTY OR PARISH 13. STATE

San Juan New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6512' KB

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

Spud & Casing Report

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well 5:00 AM on 4/4/79, ran 17 fts of 10 3/4", 40.5# Casing set at 710' KB, cemented w/700 sxs type B, 2% calcium chloride. Cement circulated.

5 1/2", 17# casing set at 9580' KB, cemented with 600 sxs of 50-50 pozmix + 2% gel, 6 1/4#/sx gilsonite, 0.2% HR-4.

Waiting on completion tools.



18. I hereby certify that the foregoing is true and correct

SIGNED

Clarence H. Brown

TITLE

President

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE 5/16/79

DATE

*See Instructions on Reverse Side

77470CC