

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well <input type="checkbox"/> gas well <input checked="" type="checkbox"/> other
2. NAME OF OPERATOR AMOCO PRODUCTION COMPANY
3. ADDRESS OF OPERATOR 501 Airport Drive Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1160' FNL x 790' FEL, Section 26, AT SURFACE: T32N, R15W AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) Spud and Set Casing	

5. LEASE M00-C-1420-1732
6. IF INDIAN, ALLOTTEE OR TRIBE NAME Ute Mountain Tribe
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME Mountain Ute Tribal "B"
9. WELL NO.
10. FIELD OR WILDCAT NAME Wildcat
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA NE/4 NE/4 Section 26 T32N, R15W
12. COUNTY OR PARISH San Juan
13. STATE NM
14. API NO. 30-045-23542
15. ELEVATIONS (SHOW DE KDB AND WD) 6687' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 12-1/4" hole on 7/26/79. Drilled to 322'. Set 8-5/8", 24# casing at 322' and cemented with 275 sx Class "B" Neat cement with 2% CaCl₂ circulated out 12 sx good cement.

Drilled 7-7/8" hole to TD and set 4-1/2", 10.5# casing at 3600'. Cemented with 170 sx Class "B" Neat cement containing 1/4# Cellophane flakes per sx and 0.8% fluid loss additive.

Rig released on 8/4/79.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

Original Signed By
SIGNED E. E. SVOBODA

TITLE Dist. Adm. Supvr. DATE 8/21/79

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE DATE

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
DURANGO, CO.

