Dec. 1973	Budget Bureau No. 42-R1424		
UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE NM-019414		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME		
reservoir, Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME		
1. oil gas well stother	Stanolind Gas Com C 9. WELL NO.		
2. NAME OF OPERATOR	1 3 4 3 4 3		
Amoco Production Company	10. FIELD OR WILDCAT NAME		
 3. ADDRESS OF OPERATOR 501 Airport Drive Farmington, NM 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 	Blanco Mesaverde-Basin Dakota 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA NW/4, SE/4, Section 17, T32N, R12W		
AT SURFACE: 1820' FSL x 1590' FEL, Section 17, AT TOP PROD. INTERVAL: Same T32N, R12W AT TOTAL DEPTH: Same	12. COUNTY OR PARISH 13. STATE San Juan NM		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	30-045-23779		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6023 GL		
TEST WATER SHUT-OFF			
REPAIR WELL	(NOTE: Report results of multiple completion or his		
PULL OR ALTER CASING MULTIPLE COMPLETE	change on Form 9-30		
CHANGE ZONES	10000		
ABANDON*			
(other) Completion			
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent	irectionally drilled, give subsurface togations and		

Completion operations began on 4-21-80. Total depth of the well is 6915' and plugback depth is 6810'. Perforated intervals from 6300' to 6305', 6307' to 6313', with 2 SPF, a total of 22, .38" holes. Perforated intervals from 6152' to 6158', 6223' to 6233', and 6237' to 6246', with 2 SPF, a total of 50, .38" holes. Sand-water fraced with 137,000 gallons of frac fluid and 369,000# of 20-40 sand. Landed 2-3/8" tubing at 6268'. Swabbed the well and released the rig on 5-9-80.

Subsurface Safety Valve: Manu. and Type					Ft.
18. I hereby certify that the foregoing is tr	rue and correct				
SIGNED E SVOLUDÁ	THILE Dist. Adm.	. Supvr. DATE	5-23-80	4 .	
	(This space for Federal or Stat	e office use)	ARAFDY	ra rad (
APPROVED BY	TITLE	DATE _	ACCEPTED FOR RECORD		
		NMOCC	MΔ	/ 29 19	180
		MMOCG.	11111	19.0 10	
			FARE	CONTRACTOR PROPERTY	110 7

*See Instructions on Reverse Side