UNITED STATES

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE SHOOT OR ACIDIZE PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give Pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give Shaurface loganous and measured and true vertical depths for all markers and zones pertinent to this work.)* 1. Set retrievable Baker Bridge Plug at 4828'. 2. Perforate Mesa Verde 4606, 08, 10, 16, 18, 28, 30, 32, 39, 41, 54, 56, 58, 60, 62, 77, 79, 90, 92, 94, 96, Total 21 holes, 3. Breakdown with 2350 gallons 15% HCL acid. Broke down at 2300# PSI, 4. Frac with 128,352 gallons 2% KCL Slickwater and 45,000# 20/40 sand, 5. Maximum pressure 2100#, 15 minute Shut-in pressure 700# Subsurface Safety Valve: Manu. and Type Set @ Ft. 18. I hereby certify that the foregoing is true and correct SIGNED WATER AND ALL STRICE SHOP THE SUPPLY STR	REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	15. ELEVATIONS (SHOW DF, KDB, AND WD) 5925' GR
18. I hereby certify that the foregoing is true and correct SIGNED WALL LINE Superintendent DATE (This space for Federal or State office use)	PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is of the complete of t	e all pertinent details, and give pertinent dates, lirectionally drilled, give subsurface locations and int to this work.)*
APPROVED BY TITLE DATE	 Perforate Mesa Verde 4606, 08, 10, 16, 18, 39, 41, 54, 56, 58, 60, 62, 77, 79, 90, 92, Breakdown with 2350 gallons 15% HCL acid. Frac with 128,352 gallons 2% KCL Slickwater 	28, 30, 32, 94, 96. Total 21 holes, Broke down at 2300# PSI, and 45,000# 20/40 sand,
CONDITIONS OF APPROVAL, IF ANY:	 Perforate Mesa Verde 4606, 08, 10, 16, 18, 39, 41, 54, 56, 58, 60, 62, 77, 79, 90, 92, 3. Breakdown with 2350 gallons 15% HCL acid. Frac with 128,352 gallons 2% KCL Slickwater 5. Maximum pressure 2100#, 15 minute Shut-in pressure 2100#, 15 minute Shut-in pressure 2100#. 	28, 30, 32, 94, 96. Total 21 holes, Broke down at 2300# PSI, and 45,000# 20/40 sand, pressure 700# Set @Ft.