Form 9-331

UNITED STATES	Budget Bureau No. 42–R1424		
	5. LEASE		
DEPARTMENT OF THE INTERIOR	SF - 078818-A		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
	N/A	TON HADE WANTE	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT	NAME	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	N/A		
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NA	MC	
1. oil gas gry	USA		
well well other	9. WELL NO.		
2. NAME OF OPERATOR	#2		
Supron Energy Corp. c/o Gordon L. Llewellyn	10. FIELD OR WILDCAT		
3. ADDRESS OF OPERATOR	Basin Dakota		
17400 Dallas Pkwy., Suite 110, Dallas, TX 75252	11. SEC., T., R., M., OR BLK. AND SURVEY OF		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	BLK. AND SURVEY OR	
Delow.)	<u>Sec. 24 T32N R13W</u>		
AT SURFACE: 930' FSL & 1050' FWL (SW SW)	12. COUNTY OR PARISH		
AT TOP PROD. INTERVAL:	San Juan		
AT TOTAL DEPTH:	14. API NO.	New Mexico	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.		
REPORT, OR OTHER DATA	1		
	15. ELEVATIONS (SHOW	DF, KDB, AND WD)	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5941' GR		
TEST WATER SHUT-OFF XX	The first of the second		
FRACTURE TREAT	والمنافعة المنافعة ا		
SHOOT OR ACIDIZE			
PULL OR ALTER CASING	(NOTE: Report results of mi	Ittiple completion or	
MULTIPLE COMPLETE	change on Form 94	3301 5	
CHANGE ZONES	OUT IC 10		
ABANDON*	COLL CON	80 1	
(other)	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		
	OIL CON. CO.	VI.	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is directly the starting any proposed work.	all pertinent details, and	ve pertinent dates	
including estimated date of starting any proposed work. If well is directly measured and true vertical depths for all markers and zones pertinent	ectionally drilled, give sub-	surface locations and	
20163 pertinent	to this work.)*		
1. Spudded 12 1/4" hole to 322' at 3:00 P.M., 8	/31/80.		
2. Nail / Julius (310) Of 8 5/8", 24# J-55 STRC casing			
2. Sec a cemented 310.	· ·		
4. Cemented w/ 250 sacks Ideal Class B, 2% A-7,	1/4# C_F		
o. Trug down at 4:00 A.M.	1/4// 0-1.		
6. Circulation good, 5 hbjs			
/. Checked water shut-off at 800# with 10" ooo	Spring Schaffen F	NT	
Preventor.	series schaffer E	slow out	
Subsurface Safety Valve: Manu. and Type	0.1.4	~	
10 thanks for a second	Set (<u> </u>	
18. I hereby certify that the foregoing is/true and correct			
SIGNE FURNIAU V. WalleyITLE Superintendent	<u> </u>	CT S 1980	
		<u> </u>	
(This space for Federal or State office	use)		
APPROVED BY TITLE	DATE		
CONDITIONS OF APPROVAL, IF ANY:	DATE		