| UNITED STATES | 5. LEASE |
|--|--|
| DEPARTMENT OF THE INTERIOR | SF - 078818A 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| GEOLOGICAL SURVEY | N/A |
| CHARRY MOTICES AND DEPORTS ON WELLS | 7. UNIT AGREEMENT NAME |
| SUNDRY NOTICES AND REPORTS ON WELLS | N/A |
| Oo not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.) | 8. FARM OR LEASE NAME. |
| | USA |
| 1. oil gas X other | 9. WELL NO. |
| 2. NAME OF OPERATOR | #2 |
| Supron Energy Corp. % John H. Hill, et al | 10. FIELD OR WILDCAT NAME |
| 3. ADDRESS OF OPERATOR Suite 020, Kysar Building | Basin Dakota |
| 3. Address of Operator Suite Geo, Nov. 1934. 34.1.33.33.33.33.33.33.33.33.33.33.33.33.3 | 11. SEC., T., R., M., OR BLK. AND SURVEY OR |
| 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 | AREA |
| t-1 \ | Sec. 24 T32N R13W |
| below.) AT SURFACE: 930' FSL & 1050' FWL (SW SW) | 12. COUNTY OR PARISH 13. STATE |
| AT TOP PROD. INTERVAL: | San Juan New Mexico |
| AT TOTAL DEPTH: | 14. API NO. |
| 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, | 4 |
| REPORT, OR OTHER DATA | 15. ELEVATIONS (SHOW DF, KDB, AND WD) |
| REPORT, OR OTHER BITT | 5941' GR |
| REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: | 100000 |
| TEST WATER SHUT-OFF | |
| FRACTURE TREAT | A Land Control of the |
| SHOOT OR ACIDIZE | (NOTE: Report results of multiple completion or zone |
| REPAIR WELL | change on Fourt 9-330.) |
| PULL OR ALTER CASING | |
| MULTIPLE COMPLETE | |
| A DANIDON * | A CONTRACTOR OF THE PROPERTY O |
| (other) Test & Squeeze Mesa Verde | |
| 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine | |
| measured and true vertical depths for all markers and zones pertine | The Court of the Morney |
| Tested Mesa Verde and recovered 100% formations from 4390' to 4498' in two stage Class B cement, ½ cu.ft. Perlite per sack & stage with 150 sx. Class B cement, ½ cu.ft. Chloride. Squeeze job tested to 1500 PSI and 3/13/81. | ges. First Stage with 150 sx. |
| Subsurface Safety Valve: Manu. and Type | |
| SIGNED WITH Superintend (This space for Federal or State | |
| TITLE | ACCEPTED FOR RECORD |
| CONDITIONS OF APPROVAL, IF ANY: | MAR 2 4 1981 |