

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Southland Royalty Company

3. ADDRESS OF OPERATOR
P.O. Drawer 570, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 930' FNL & 990' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

(other) Perforation & Stimulation ☒
Production Tubing Report ☒

5. LEASE

SF-078146

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hillstrom

9. WELL NO.

3

10. FIELD OR WILDCAT NAME

Blanco Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 35, T32N, R12W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6333' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 9-02-81 Perforated Pictured Cliffs at 2694', 2700', 2759', 2777', 2782', 2795', 2801', 2831', 2837', 2843', 2849', 2855', 2861', 2867' and 2873'. Total of 15 holes. Frac'd with 88,942 gallons fresh water and 79,000# of 20/40 sand. AIR 30 BPM, ATP 1800 psi, ISIP 700 psi. Perforated Fruitland at 2430', 2437', 2443', 2473', 2590' and 2602'. Total of 6 holes. Frac'd with 41,140 gallons of fresh water and 29,000# of 20/40 sand. AIR 12 BPM, ATP 3100 psi, ISIP 1500 psi.
- 9-04-81 Ran 85 joints (2827') of 1-1/2", 2.90#, J-55, EUE tubing set at 2838'. Packer set at 2638'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Cathy Greyeyes TITLE Drilling Clerk DATE September 4, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE SEP 9 1981
CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side

BY SM