

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
Sundry Notices and Reports on Wells

1. Type of Well

Gas

2. Name of Operator

Texas Pacific Oil & Gas Co., C/O Joseph E. Seagrams & Sons, Inc.

3. Address & Phone No. of Operator

800 3<sup>rd</sup> Ave., New York City, NY 10022-7699

4. Location of Well, Footage, Sec., T, R, M

790' FNL and 1826' FWL Sec.28, T-32-N, R-17-W, NMPM

C

5. Lease Number  
14-20-603-5012

6. If Indian, All. or  
Tribe Name  
Navajo

7. Unit Agreement Name  
N/A

8. Well Name & Number  
Navajo #17

9. API Well No.  
30-045-2542700

10. Field and Pool  
Many Rocks

11. County & State  
San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

Texas Pacific Oil and Gas Co., proposes to Plug and Abandon this well per the attached procedure and diagram.

RECEIVED  
MAR - 3 1997

CHL CON. DIV.  
DIST. 3

070 MAR 10 1997  
57 FEB 25 11 08 17

14. I hereby certify that the foregoing is true and correct.

Signed William F. Clark Title Contractor  
William F. Clark, A-Plus Well Service

Date 2/24/97

(This space for Federal or State Office use)

APPROVED BY /s/ Duane W. Spencer Title \_\_\_\_\_

Date FEB 27 1997

CONDITION OF APPROVAL, if any:

NMOCD

# Navajo #17

## Proposed P&A

Many Rocks Gallup

790°N, 1826°W Sec 28, T-32-N, R-17-W, San Juan County, NM

Today's Date: 2/19/97

Spud: 7/28/82

Completed: 8/15/82

Point Lookout @ Surface

Gallup @ 1370'

Sanostee Lime @ 1724'

9" Hole

6-1/4" Hole

TD 1733'

7" 22# Casing Set @ 62'  
Cmt with 8 cf (Circulated to Surface)

Perforate at 112'

Plug #2 112' - Surface  
Cmt with 20 sxs Class B.

TOC @ 1259' (Calc, 75%)

Plug #1 1733' - 1320'  
Cmt with 64 sxs Class B  
(50% excess, long plug)

4-1/2" 9.5# Csg @ 1690'  
Cemented with 59 cf

Gallup Open Hole Interval:  
1705' - 1723'

### Well History:

7" 22# surface csg set at 62' cemented to surface with 8 cf.

4-1/2" 9.5# csg set at 1690' with 50 sxs cement.

Gallup zone open hole interval 1705' - 1690'.

2-3/8" tubing at 1705'.

### Proposed Plugging Procedure:

1. POH with tubing. RIH and tag bottom. Plug #1 from 1733' to 1320' with 64 sxs Class B cement. POH with tubing.
2. WOC and then RIH and tag cement. Pressure test casing to 300#. POH with tubing.
3. RIH and tag cement. Perforate 2 squeeze holes at 112'. Establish circulation out bradenhead. Mix and pump 20 sxs Class B cement from 112' to surface, circulate good cement out bradenhead.
4. WOC, cut off wellhead and install P&A marker.