

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
WTR Oil Company

3. ADDRESS OF OPERATOR
Drawer LL, Cortez, Colo 81321

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 330' FWL, 2309' FNL Unit E, Sec. AT SURFACE: 35, T32N, R17W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- REQUEST FOR APPROVAL TO:
- TEST WATER SHUT-OFF
 - FRACTURE TREAT
 - SHOOT OR ACIDIZE
 - REPAIR WELL
 - PULL OR ALTER CASING
 - MULTIPLE COMPLETE
 - CHANGE ZONES
 - ABANDON*
 - (other) New Well

SUBSEQUENT REPORT OF:

-
-
-
-
-
-
-
-
-

RECEIVED

OCT 08 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE

14-20-600-3540

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Navajo P

9. WELL NO.

17

10. FIELD OR WILDCAT NAME

Gallup Many Rocks

11. SEC., T., R., M., OR BLK. AND SURVEY OR

AREA SW $\frac{1}{4}$, NW $\frac{1}{4}$ - Sec 35
T32N - R17W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

GL 5786.1

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded in 7:30 A.M. 9-24-82. Set 80' 20# 7" surface aet at 83' GL. Mix 50sk (59cuft) Cl. B 2% CaCl + $\frac{1}{4}$ # Gil./sk. Cir. 18.5 cuft cement. Plug down 12:00 Noon. W.O.C. 8 hrs - test B.O.P. and casing to 500 psi and held.

TD 1768 9-26-82

Logged to surface.

Ran 43 jts. 9.5# 4 $\frac{1}{2}$ " casing (1754.04) landedd at 1754 GL - Mixed 160 sks (205 Cu/Ft) 50/50 Poz - 2% Gel - 10% salt - 2% CaCl - Tailed in with 50sks (59cuft) Class B - 2%CaCl - Circulated $\frac{1}{2}$ BBL (3cuft). Plug Down at 8:30 A.M. 9-27-82.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Lee E. Searay TITLE Office Manager DATE 10-4-82

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

ACCEPTED FOR RECORD

OCT 15 1982

*See Instructions on Reverse Side

NMOCC

FARMINGTON, N.M.

BY Jm