STATE OF NEW MEXICO

OIL CONSERVATION DIVISION

Page Revised 10/01/

pecker	ptivis resorting leanage tests ast New Mexico	NORTHWEST N	EW MEXICO PA	ACKER-LEAKA	ge test A	PI# 30-045- 2566
Operator <u>&</u>	surling to.	4			_	Well 7
- F	M Sec. // 1					San Juan
NAME OF RESERVOIR OR POOL			TYPE OF PF	100.	METHOD OF PROD. (Flow or Art. Lift)	PROD, MEDIUM (Thg. or Cog.)
Upper Jru	istand ?	Sand	Mas	(none	TB9.
Lower Completion	sterred (lisso_	Sas	/	How	TBq.
1,1,12		PRE-FLO	OW SHUT-IN P	RESSURE DATA		
Upper Hour, date Completion 14:00	,	Length of time shu		81 press. psig 43 9		Tabilized? (Yes or No)
Hour, date shul-in Length of		Longth of time and			17	Stabilized7(Yes or No) Yes
7,00			FLOW TEST	NO. 1		
Commenced at theur,	date) 🕈			Zane producing (U	leger or Lowerk	
TIME (hour, date)	LAPSED TIME	Upper Completion	Lawer Comptetion	PROG. ZONE TEMP.		REMARKS
4-11	4 days	250	335		WillAnd	ed by Heary Yeva NMOCH
D7.30					Verted to atm	Upper Bone 10250,
				0111233	NO L	eak detected
			j.	(C) (V) (A)		
			6	APR 2000		
				04.634.00		
Production rate	during test	<u> </u>	Ţ.			•
	BOF	D based on	Bbls. i	Con the second	ss. G	ravGOR
					ter):	
5 			EST SHUT-IN F	RESSURE DATA	A	
Upper Hour, date shut-in Length of time s				Si press. psig Stabilized? (Y		Stabilized? (Yes or No)
Completion Hour, de	ste shutin	Length of time si	Length of time shut-in		 	Stabilized? (Yes or Ho)

FLOW TEST NO. 2

POSSELLAS

Zone producing (Upper or Lewer):

TIME	LAPSED TIME SINCE ##	PRESSURE		PROD. ZONE	
(hour, date)		Upper Completion	Lower Completion	TEMP.	REMARKS
					
					·
	,		•		
·			,		·
			-		
				<u> </u>	
					Grav GOR):
			rd: lested unu	(Office of Meter));
marks:					
ereby certify th	at the information	n berein contain	ed is true and con	nplete to the best	t of my knowledge.
proved	·		_19 O	perator	ORK BeHale BR
New Mexico Oil	Conservation D	ivision	В	Mae	K' Bettale
090				ide Lease	Operator Signed By Do
	TY ON A BALL ON	PERMENTAL MIT &	,	ate4.	11-112
1C			· D•	aea ~~~~	~// - W//

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the rubing have been disturbed. Term shall also be taken at any time that communication is suspected or when requested by the Division.

d at (howr, date) 🕈 🕈

- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is so be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previous ly shot-in is produced.
- 7. Pressures for gas-some cests must be measured on each some with a deadweight pressure gauge at time intervals as follows: 3 hours sess: immediately prior to the beginning of each flow-period, at lifeen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the asion of each flow period. 7-day teru: immediately prior to the beginn of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previous wir shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which smart be checked at least twice, once at the beginning and once at the end of each test, with a dendweight pressure gauge, if a well is a gas-oil or an oil-gas dual exempterion, the recording gruge shall be required on the oil zone only, with deadweight pressures as requir above being taken on the gas zone.

8. The results of the shave-described tests shall be filed in triplicate within 15 days after pletion of the rest. Tests shall be filed with the Aztre District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Tex Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas some only) and gravity and GOR (oil zones only).