Form 9-331 Dec. 1973

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

		Form Approved. Budget Bureau No. 42–RI424	
	5. LEASE		
١	SF 078146	)	
	6. IF INDIAN, AL	LOTTEE OR TRIBE NAME	
	7. UNIT AGREE	MENT NAME	
_	8. FARM OR LEA		
	Newberry		
_	9. WELL NO.	and the second of the second o	
	14 10. FIELD OR WILDCAT NAME		
_	Blanco Pictured Cliffs Ext.		
		M., OR BLK. AND SURVEY OR	
-		34, T-32-N, R-12-W	
	N.M.P.M.		
		PARISH 13. STATE	
	San Juan	New Mexico	
_	14. API NO.		
	15. ELEVATIONS (SHOW DF, KDB, AND WD		
	6128' GL	· · · · · · · · · · · · · · · · · · ·	
۲	* <b>*</b> / 10 m		
i	change or	sults of multiple completion or zone n Form 9–330.)	
	Halifa in APHA		
at	ate all pertinent deta	ails, and give pertinent dates	
d	directionally drilled.	give subsurface locations and	

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas K other	Newberry  9. WELL NO.
2. NAME OF OPERATOR	14
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Blanco Pictured Cliffs Ext.
Box 4289, Farmington, New Mexico 87499	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec. 34, T-32-N, R-12-W
	N.M.P.M.
below.) AT SURFACE: 1535'N, 1830'W	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	San Juan New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REPORT, OR OTHER DAM	i i i i i i i i i i i i i i i i i i i
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6128' GL
FRACTURE TREAT	NAME OF THE PERSON OF THE PERS
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330.)
MULTIPLE COMPLETE	
CHANGE ZONES	
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner	irectionally drilled, give subsurface locations and
10-21-83 Tested casing to 4000# O. K. P.B.T.D. 2769'. Perforated 2522, 25 2621, 2626, 2632' w/1 SPZ. Fracture 68,100 gallons slick water. Dropped Flushed w/630 gallons water.	d w/61,000# 10/20 sand and
riusiled w/ 050 garrons water.	- FARINCA
	DECEMBINE
·	
M .	
	<b>Di</b> Question of the second
Subsurface Safety Valve: Manu. and Type	Set @ Ft
18. I hereby certify that the foregoing is true and correct	0 1 06 1007
SIGNED M. J. Susco TITLE Drilling Cle	DATACCEPTED FOR RECORD
(This space for Federal or State of	
APPROVED BY TITLE	DATE 007 28 1983
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE
· ** O COLOR	FAR AREA
	GY