

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved.  
Budget Bureau No. 42-R1424

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☒ well other ☐  
2. NAME OF OPERATOR  
LOBO PRODUCTION  
3. ADDRESS OF OPERATOR  
P.O. Box 2364, Farmington, New Mex 87499  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 935' FNL & 810' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
USA SF 078818-A  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
N/A  
7. UNIT AGREEMENT NAME  
N/A  
8. FARM OR LEASE NAME  
SCORPIO  
9. WELL NO.  
# 1  
10. FIELD OR WILDCAT NAME  
WC/Gallup/ Basin Dakota  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 15, T 32N, R 13W  
12. COUNTY OR PARISH  
San Juan  
13. STATE  
New Mex.  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6004.0 Gr.

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.) JUN 08 1984

BUREAU OF LAND MANAGEMENT  
FARMINGTON RESOURCE AREA

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

May 25-1984-Four Corners Drilling moved on location. Rig # 12 spud well at 4:00pm.  
Drilled to 235'. Ran 5 jts. 9 5/8" 36# casing. Set at  
225' KB. Surface Cement: 120 sks. Cls.B with 3 sks. CaCl (126.0 cu.ft.)

June 1, 1984-Ran 65 jts. 7" 23# J-55 casing. Set at 2652'. Ran CND, DIL Logs.

June 2, 1984-Cemented with 325 sks. Halco lite, 1/4# flocele 12.8#/gal.(383.50 cu.ft.)  
Tailed with 125 sks. Cls. B w/2% CaCl 1/4# flocele 15.8 p/gal.  
(146.50 cu.ft.) Plug down 7:10am. WOC 12 hours.

June 5, 1984-T.D. 4645'. WOC.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE \_\_\_\_\_ DATE \_\_\_\_\_

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE Operator DATE 6-5-84  
CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_

ACCEPTED FOR RECORD

JUN 19 1984

\*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA

RV Sm

NMOCC